Product datasheet

Specifications



Acti9, Linear switch - iSSW - 2 C/O - 20A - 250 V AC - 2 positions

A9E18071

Main

| Range of product | Acti9 |
|--------------------------------|------------------------------|
| Product name | Acti9 iSSW |
| Product or component type | Linear switch |
| Device short name | iSSW |
| Device application | Electrical circuit control |
| Contacts type and composition | 2 C/O |
| [Ue] rated operational voltage | 250 V AC 50/60 Hz |
| Standards | IEC 60669-1 IEC 60947-5-1 |

Complementary

| [le] rated operational current | 20 A |
|--------------------------------|--|
| Control type | Toggle 2 positions |
| Marking | 0 - 1 |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| 9 mm pitches | 4 |
| Height | 82 mm |
| Width | 36 mm |
| Depth | 75 mm |
| Colour | White |
| Electrical durability | AC-22: 30000 cycles cos Phi = 0.8 |
| Connections - terminals | Staggered tunnel terminal (downside) 2 cable(s) 0.52.5 mm² flexible Staggered tunnel terminal (downside) 2 cable(s) 0.52.5 mm² rigid without cable end |
| Wire stripping length | 9 mm |
| Tightening torque | 1 N.m |

Environment

| IP degree of protection | IP20 conforming to IEC 60529 |
|-------------------------|------------------------------|
| Tropicalisation | 2 |

| Pollution degree | 3 |
|---------------------------------------|---------------|
| Relative humidity | 95 % at 55 °C |
| Ambient air temperature for operation | -2050 °C |
| Ambient air temperature for storage | -4070 °C |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|----------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8 cm |
| Package 1 Width | 3.5 cm |
| Package 1 Length | 7.5 cm |
| Package 1 Weight | 88 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 9.6 cm |
| Package 2 Width | 8 cm |
| Package 2 Length | 23 cm |
| Package 2 Weight | 594 g |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 54 |
| Package 3 Height | 30 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 5.888 kg |
| | |

Offer Sustainability

| REACh Regulation | REACh Declaration |
|----------------------------|---|
| REACh free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| RoHS exemption information | Yes |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

Warranty 18 months

Recommended replacement(s)