

Product datasheet

Specifications



VTPN Distribution board, Acti9, 8 ways, 250A MCCB, double door metal, IP43

A9HVN08H

Main

Range	Acti9
Product name	VTPN
Product or component type	Consumer unit
Device application	Distribution
Colour	White (RAL 9003)
Provided equipment	Removable gland plates Removable centre plates Earthing bar Neutral bar Fishbone busbar Busbar link Cable shroud
Door type	Plain

Complementary

Enclosure mounting	Flush Surface
Protection device type	Main incomer: molded case circuit breaker (MCCB) - 3P or 4P - 250 A Outgoer: miniature circuit breaker (MCB) - 1P or 3P - 63 A
[Icw] rated short-time withstand current	25 kA for 0.5 s
[In] rated current	250 A
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Total number of 18 mm modules	24
Number of ways	8 ways
Enclosure/Cubicle description	Double door enclosure
Enclosure material	Galvanized steel box Galvanized steel cable gland plate Galvanized steel mounting plate CRCA door CRCA central plate
Door opening side	Reversible
Height	667 mm external:
Width	416 mm external:
Depth	155 mm external:

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net weight	17.5 kg
Environment	
IP degree of protection	IP43
IK degree of protection	IK09
Standards	IS 8623-1 IS 8623-3 IEC 61439-3
Product certifications	NABL
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.5 cm
Package 1 Width	66.7 cm
Package 1 Length	41.6 cm
Package 1 Weight	18.5 kg
Offer Sustainability	
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes

Recommended replacement(s)