Product datasheet

Specifications



Acti 9 K60H 4P - 6 A - C curve 10 kA - set of 3

A9KF71406BQ

Main

Distribution
Acti9
Acti9 K60
Miniature circuit-breaker
К60Н
4P
4
6 A
AC
Thermal-magnetic
С
10000 A Icn at 415 V AC 50/60 Hz conforming to EN 60898-1 10000 A Icn at 415 V AC 50/60 Hz conforming to IEC 60898-1
Yes
EN 60898-1 IEC 60898-1
ISI

Complementary

Network frequency	50/60 Hz
Magnetic tripping limit	510 x ln
[Ics] rated service breaking capacity	10 kA 75 % conforming to EN 60898-1 - 415 V AC 50/60 Hz 10 kA 75 % conforming to IEC 60898-1 - 415 V AC 50/60 Hz
Limitation class	3 conforming to EN 60898-1
[Ui] rated insulation voltage	500 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	4 KV
Contact position indicator	No
Control type	Toggle
Local signalling	Without
Mounting mode	Fixed
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Downstream: biconnect

9 mm pitches	8
Height	81 mm
Width	72 mm
Depth	70 mm
Net weight	0.48 kg
Quantity per set	Set of 3
Colour	White
Mechanical durability	20000 cycles
Electrical durability	20000 cycles
Connections - terminals	Tunnel type terminals (downstream) 125 mm² rigid Tunnel type terminals (upstream) 125 mm² rigid Tunnel type terminals (downstream) 116 mm² flexible Tunnel type terminals (upstream) 116 mm² flexible
Wire stripping length	14 mm for top or bottom connection
Tightening torque	2 N.m top or bottom
Earth-leakage protection	Without

Environment

IP degree of protection	IP20 conforming to IEC 60529
Pollution degree	2 conforming to IEC 60898-1 2 conforming to EN 60898-1
Overvoltage category	II
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Operating altitude	02000 m
Ambient air temperature for operation	-555 °C
Ambient air temperature for storage	-2585 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.2 cm
Package 1 Width	9.2 cm
Package 1 Length	22.8 cm
Package 1 Weight	1.3 kg

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations