Product datasheet

Specification





iQuick PRD8r modular surge arrester - 3 poles + N - 350V - with remote transfer

A9L16300

Main

range of product	Acti9	
Product name	Acti9 iQuick PRD	
Product or component type	Surge arrester with pluggable cartridge	
Device short name	iQuick PRD8r	
Device application	Distribution	
Standards	EN 61643-11:2012 IEC 61643-11:2011	
Product certifications	CE	
Quality labels	KEMA-KEUR NF	
poles description	3P + N	
Remote signalling	With	
Signal contacts composition	1 SD (1 C/O)	
Surge arrester type	Electrical distribution network	
Earthing system	TT TN-S	

Complementary

Complementary	
Surge arrester class type	Type 2 + 3
Surge arrester technology	MOV + GDT
[Ue] rated operational voltage	230/400 V AC (+/- 10 %) at 50/60 Hz
[In] nominal discharge current	Common mode: 2 kA (L/PE) Common mode: 2 kA (N/PE) Differential mode: 2 kA (L/N)
[Imax] maximum discharge current	Common mode: 8 kA L/PE Common mode: 8 kA N/PE Differential mode: 8 kA L/N
[Uoc] open circuit voltage	10 kV type 3 common mode L/PE 10 kV type 3 common mode N/PE 10 kV type 3 differential mode L/N
[Uc] maximum continuous operating voltage	Common mode: 264 V N/PE Common mode: 350 V L/PE Differential mode: 350 V L/N
Maximum [Up] voltage protection level	Common mode <1.5 kV type 2 L/PE Common mode <1.7 kV type 2 N/PE Differential mode <1.2 kV type 2 L/N Common mode <1.4 kV type 3 L/PE Differential mode <1.4 kV type 3 L/N

Common mode <1.5 kV type 3 N/PE

Disconnector device type	Integrated circuit breaker - Icu 25 kA	
Signalling circuit voltage	2 A/250 V AC 50/60 Hz	
Mounting mode	Clip-on (DIN rail)	
9 mm pitches	14.6	
Height	94 mm	
Width	131.5 mm	
Depth	75.9 mm	
Net weight	0.84 kg	
Colour	White (RAL 9003)	
Connections - terminals	Tunnel type terminal (downside) 2.525 mm ² Tunnel type terminal (upside) 2.525 mm ²	
Tightening torque	2.5 N.m	

Environment

IK degree of protection	IK05 conforming to IEC 62262
Relative humidity	595 %
Operating altitude	2000 m
Ambient air temperature for operation	-2560 °C
Ambient air temperature for storage	-4070 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.0 cm
Package 1 Width	10.0 cm
Package 1 Length	15.0 cm
Package 1 Weight	874.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	12
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	11.083 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations