

Product datasheet

Specifications



iPRC - 2 poles - 0.45 A - 130 V AC

A9L16337

Main

range of product	Acti9
Product name	Acti9 iPRC
Device short name	iPRC
Product or component type	Surge arrester
number of protected lines	2
Surge arrester type	Telecom protection

Complementary

Remote signalling	Without
Surge arrester technology	GDT + diode
[In] rated current	0.45 A at 45 °C
[Ue] rated operational voltage	130 V AC
Nominal discharge current	Common mode: 10 kA (L/PE) Differential mode: 10 kA (L/N)
[Iimp] impulse current	100 A
[Uc] maximum continuous operating voltage	Common mode: 130 V AC L/PE Common mode: 185 V DC L/PE Differential mode: 130 V AC L/N Differential mode: 185 V DC L/N
Maximum [Up] voltage protection level	Differential mode <160 V type 2 L/N Common mode <200 V type 2 L/PE
Output voltage limits	Common mode: < 300 V at 1 kV/μs Differential mode: < 300 V at 1 kV/μs
[I total] discharge current	10 kA
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	90 mm
Width	18 mm
Depth	66 mm
Net weight	25 g
Colour	White
Material	PA6
Response time	< 500 ns

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connections - terminals	Screw clamp terminal0.2...4 mm² rigid Screw clamp terminal0.2...2.5 mm² flexible Screw clamp terminal0.2...2.5 mm² flexible with ferrule
Wire stripping length	8 mm
Tightening torque	0.8 N.m

Environment

Standards	EN 61643-21 IEC 61643-21
Product certifications	xDSL compliance
IP degree of protection	IP40 (modular enclosure) conforming to IEC 60529 IP20 conforming to IEC 60529
IK degree of protection	IK05 conforming to IEC 62262
Relative humidity	5...90 %
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	6.7 cm
Package 1 Length	9.5 cm
Package 1 Weight	69.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	108
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	7.939 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability



Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Mercury Free	
 Rohs Exemption Information	Yes
Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins