Product datasheet

Specification





energy sensor, PowerTag Flex 230V 63A 1P+N top and bottom position

A9MEM1560

Main

Mani	
Range of product	PowerLogic
Product name	PowerTag A9 F63
Product or component type	Energy sensor
Poles	1P + N
Maximum current [Imax]	63 A
[lb] Basic current	10 A
Starting current	40 mA
Saturation current	130 A
Product specific application	Cost allocation
	Load monitoring
	Circuit monitoring
	Overload alarm
	Energy management
-	
Concentrator compatibility	Acti9 Smartlink SI B
	Acti9 Smartlink SI D
	Acti9 PowerTag Link C
	•
	Actio PowerTag Link
	Acti9 PowerTag Link HD
	Harmony Hub
	Wiser IP module
	EcoStruxure Panel Server Universal
	EcoStruxure Panel Server Advanced
	PrismaSet Active
Range compatibility	Acti 9 Acti9 iCV40
nango companionity	
	Acti 9 Vigi iC40
	Acti 9 Vigi iC60
	Acti 9 Acti9 iDD40 XA
	Acti 9 Acti9 iCV40 XA
	Acti 9 Vigi iDT40
type of measurement	Active energy
type of meddarement	Current
	Voltage
	Power factor
	Active power
Accuracy class	Class 1 current conforming to IEC 61557-12
•	Class 0.5 voltage conforming to IEC 61557-12
	Class 1 active power conforming to IEC 61557-12
	Class 1 active energy conforming to IEC 61557-12
	Class 1 power factor conforming to IEC 61557-12
	Class 1 power factor comorning to 120 01337-12
Mounting location	Top or bottom
Mounting support	On circuit breaker
Product destination	Switchboard
Event management	Voltage loss with measured current at voltage loss
Transmission support medium	Radio frequency 2.42.4835 GHz conforming to IEEE 802.15.4

Emission power 10 mW

Complementary

By screws (terminals)
Wires with cable end
1 rigid cable 1.516 mm² 2 stranded cable 1.52.5 mm² 2 rigid cable 1.52.5 mm² 1 stranded cable 1.516 mm²
0.25 m
200240 V AC, +/- 20 %
1 x 0.33 mm²
50 Hz 60 Hz
1 VA
IEC 61557-12 IEC 61010-1 IEC 61010-2-030 IEC 61326-1 ETSI EN 300 328 ETSI EN 301 487-1
Sensor element: 20 mm
Sensor element: 18 mm
Sensor element: 44.5 mm
16 g

Environment

Quality labels	CE
Directives	2014/53/EU - radio equipment directive
Operating altitude	02000 m
Ambient air temperature for operation	-2560 °C
Ambient air temperature for storage	-4085 °C
Overvoltage category	III conforming to IEC 61010-1
Measurement category	Category III conforming to IEC 61010-2-030
IP degree of protection	IP20 conforming to IEC 60529
IK degree of protection	IK05
Pollution degree	3
Relative humidity	095 % at 45 °C conforming to IEC 60721-3-3
Vibration resistance	3M4 conforming to IEC 60721-3-3
Electromagnetic compatibility	Industrial electromagnetic environment conforming to IEC 61326-1 Radiated EMC conforming to ETSI EN 301 489-17 Electromagnetic emission conforming to IEC 62311
environmental characteristics	Dustproof class 3S3 conforming to IEC 60721-3-3 Salt mist class 3C2 conforming to IEC 60721-3-3 Indoor use

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	6.000 cm
Package 1 Length	8.500 cm
Package 1 Weight	44.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	48
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	2.463 kg

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

02-Aug-2024