



Acti9 - earth leakage circuit breaker - DPN Vigi - 1P + N - 20A - 300mA

A9N19645

① Discontinued on: 15 December 2021

! Discontinued

Main

Circuit breaker application	Distribution
Range	Acti9
Product or component type	Earth leakage circuit breaker
Product name	DPN Vigi
Device short name	DPN N Vigi
Poles description	1P + N
Neutral position	Left
Number of protected poles	1
[In] rated current	20 A at 30 °C
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	С
Earth-leakage sensitivity	300 mA
Earth-leakage protection time delay	Instantaneous
Туре	Type A-SI (Super Immunised)
Breaking capacity	6000 A Icn at 230 V AC conforming to EN 61009

Complementary

Device location in system	Outgoer
[Ue] rated operational voltage	230 V AC
Magnetic tripping limit	510 x ln
Residual current tripping technology	Voltage independent
[lcs] rated service breaking capacity	6000 A at 230 V AC 50/60 Hz conforming to EN 61009
Limitation class	3 conforming to EN 61009
[Ui] rated insulation voltage	400 V AC conforming to EN 61009
[Uimp] rated impulse withstand voltage	4 kV conforming to EN 61009

Contact position indicator	Yes
Control type	Toggle
	ON/OFF indication
Local signalling	
Mounting support	DIN rail
9 mm pitches	4
Net weight	0.19 kg
Embedding depth	72 mm
Colour	White
Mechanical durability	20000 cycles
Electrical durability	20000 cycles conforming to IEC 61009
Connections - terminals	Tunnel type terminals1 cable(s) 10 mm² flexible Tunnel type terminals1 cable(s) 16 mm² rigid
Earth-leakage protection	Integrated
Environment	
Standards	EN/IEC 61009-1 EN/IEC 61009-2-1
Pollution degree	3 conforming to EN 61009
Overvoltage category	III
Tropicalisation	2 conforming to EN 61009
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-2560 °C
Ambient air temperature for	-4060 °C
storage	
Dooking Units	
Packing Units Unit Type of Package 1	Db
Number of Units in Package 1	1
	7.5 cm
Package 1 Height	
Package 1 Width	3.6 cm
Package 1 Length	8.5 cm
Package 1 Weight	208 g
Offer Sustainshility	
Offer Sustainability Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant
LO NOTIO DIFECTIVE	EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and
	never end up in rubbish bins

Halogen content performance Halogen free plastic parts product

Contractual warranty

18 months

Recommended replacement(s)

Warranty