Specifications





# Auxiliary contact, Acti9, OF, 1 C/O, 2mA to 100mA, 24VAC to 250VAC, 24VDC to 220VDC, bottom connection

A9N26914

#### Main

| Acti9                           |
|---------------------------------|
| OC contact                      |
| OF                              |
| 1 C/O                           |
| 2100 mA at 24240 V, AC 50/60 Hz |
| 2100 mA at 24 V, DC             |
| 2100 mA at 48 V, DC             |
| 2100 mA at 60 V, DC             |
| 2100 mA at 130 V, DC            |
| 2100 mA at 220 V, DC            |
| 1                               |
| EN/IEC 60947-5-1                |
| EN/IEC 60947-5-4                |
| GB/T 14048.5                    |
| GB/T 14048.17                   |
| CE                              |
| UKCA                            |
| EAC                             |
| CCC                             |
|                                 |

### Complementary

| Operating mode                                      | Daisy chain up to 100 devices  |
|---|--|
| [Ui] rated insulation voltage                       | 500 V  |
| [Uimp] rated impulse withstand voltage              | 4 kV   |
| Mounting mode                                       | Clip-on  |
| Mounting location                                   | Left side of circuit-breaker   |
| Mounting support                                    | DIN rail   |
| Comb busbar and distribution<br>block compatibility | Top: YES   |
| Height  | 85.3 mm  |
| Width   | 9 mm   |
| Depth   | 68 mm  |
| Net weight  | 30 g   |
| Colour  | White  |
| Connections - terminals                             | Screw clamp terminal (bottom) 1 cable(s) 0.52.5 mm² - rigid<br>Screw clamp terminal (bottom) 2 cable(s) 1.5 mm² - flexible<br>Screw clamp terminal (bottom) 2 cable(s) 1.5 mm² - flexible with ferrule |
| Wire stripping length                               | 9 mm   |

Tightening torque

1 N.m bottom

#### Environment

| IP degree of protection               | IP20     |
|---------------------------------------|----------|
| Pollution degree                      | 3        |
| Tropicalisation                       | 2        |
| Ambient air temperature for operation | -2570 °C |
| Ambient air temperature for storage   | -4085 °C |

## **Packing Units**

| - |
|---|

### Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration                        |
|--------------------------|--|
| Eu Rohs Directive        | Compliant<br>EU RoHS Declaration         |
| China Rohs Regulation    | China RoHS declaration                   |
| Environmental Disclosure | Product Environmental Profile            |
| Circularity Profile      | No need of specific recycling operations |