

Product datasheet

Specifications



Acti 9 Isolator xSW 3P 63A 2.5kA 415V AC

A9S3P063

Main

Range of product	ISW 40...125
Range	Acti9
Product or component type	Isolator
Device application	Isolation

Complementary

[Ie] rated operational current	63 A at 415 V AC
[Ui] rated insulation voltage	6 kV
[Uimp] rated impulse withstand voltage	500 V
Poles description	3P
Rated breaking capacity	2.5 kA
Short-circuit withstand	20 A
[Us] rated supply voltage	48 V DC 1P 100 V DC 2P
Utilisation category	AC-22
Total number of 18 mm modules	3
Product destination	Distribution board

Environment

Ambient air temperature for operation	-20...50 °C
Pollution degree	3
Standards	IEC 60947-3 IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8 cm
Package 1 Width	7 cm
Package 1 Length	8 cm

Package 1 Weight	0.264 kg
------------------	----------

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes

Recommended replacement(s)