Product datasheet

Specifications

Green Premium™

Opale Keytag switch Mechanical type 20A

AAKX6005

⚠ Discontinued on: 30-Jun-2023

⚠ **To be discontinued**

Main

Range	Opale
Product or component type	Key card switch
Device application	Control
device presentation	Mechanism
Light source	Neon
Colour tint	White

Complementary

Technology type	Electromechanical
Device mounting	Flush
Number of modules	2 modules
Actuator	Rocker
Switch function	1-way
Rated current	20 A
[Ue] rated operational voltage	240 V
Lamp function	Indicator
Network type	AC
Network frequency	50 Hz
Fixing mode	By captive screws
Connections - terminals	Shrouded terminals
Material	PC: front cover PA6: base cover
Height	90.3 mm
Width	90.3 mm
Depth	44.5 mm

Environment

Standards	IS 3854:1997/A1
IP degree of protection	IP20
Ambient air temperature for operation	-5…35 °C
Relative humidity	10…95 %

Life Is On | Schneider Electric

Environmental characteristic	Indoor use

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.000 g

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency   RoHS/REACh

Well-being performance

✔ Reach Free Of Svhc

✔ Toxic Heavy Metal Free

✔ Mercury Free

✔ Rohs Exemption Information   Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations