Product datasheet

Specifications

Green Premium™

Opale cover frame 8 module with fixing frame 8 module CG - Square

AAKY0809

⚠ Discontinued on: 30-Jun-2023

⚠ **To be discontinued**

Main

Range	Opale
Product or component type	Cover frame with fixing frame
Colour tint	Coke grey
Material	ABS + PC: front cover ABS (acrylonitrile butadiene-styrene): base cover

Complementary

Device mounting	Flush
Number of modules	8 modules
Range compatibility	Opale switch and socket-outlet
Surface finish	Satin
Height	153.2 mm
Width	147 mm
Depth	13 mm

Environment

IP degree of protection	IP20
Environmental characteristic	Indoor use
Ambient air temperature for storage	-5…35 °C
Relative humidity	10…95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.3 cm
Package 1 Width	15.3 cm
Package 1 Length	1.3 cm
Package 1 Weight	86 g
Unit Type of Package 2	BB1
Number of Units in Package 2	30
Package 2 Height	250 cm

Package 2 Width	265 cm
Package 2 Length	335 cm
Package 2 Weight	2585 g

Life Is On | Schneider Electric

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium ›

Guide to assess a product's sustainability ›

Transparency   RoHS/REACh

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information   Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations