Product datasheet





voltage transformer - 230..400 V -1 x 115 V - 1000 VA

ABL6TS100G

- ! Discontinued on: 5 Apr 2023
- ! To be end-of-service on: 1 June 2025

(!) Discontinued

Main

Range Of Product Modicon Transformer Optimized			
Product Or Component Type	Safety and isolation transformer		
Rated Power In Va	1000 VA		
Input Voltage	230 V AC single phase, terminal(s): N-L1 400 V AC phase to phase, terminal(s): L1-L2		
Output Voltage	115 V AC		
Secondary Winding	Single		
Protective Cover	Without		
Ambient Air Temperature For	-2050 °C		

Complementary

Complementary	
Input Voltage Limits	207253 V 360440 V
Network Frequency Limits	4763 Hz
Input Voltage Tolerance	+/- 15 V
Efficiency	94 %
Power Dissipation In W	63.8 W
Output Sustained Overvoltage	3 % (no load, hot state)
Maximum Voltage Drop At Rated Load	0.5 %
No Load Losses	26.5 W
Short-Circuit Voltage	0,0304
Output Protection Type	Against overload, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection
Connections - Terminals	For input connection: screw type terminals, connection capacity: 5 x 4 mm² AWG 11 For input ground connection: screw type terminals, connection capacity: 1 x 4 mm² AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² AWG 11
	CE
Fixing Mode	By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on vertical panel, operating position: vertical By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %
Operating Altitude	3000 m

Life Is On Schneider 17 Apr 2024



Electrical Insulation Class	Class B
Width	174.0 mm
Height	138.0 mm
Depth	163.0 mm
Net Weight	13.66 kg

Environment

Product Certifications	EAC	
	UR	
	DNV-GL	
Standards	UL 506	
Ip Degree Of Protection	IP20	
Environmental Characteristic	EMC conforming to EN 62041	
	Safety conforming to EN 61558-1	
	Safety conforming to EN 61558-2-4	
Protective Treatment	тс	
Ambient Air Temperature For Storage	-4080 °C	
Overvoltage Category	Class I conforming to VDE 0106-1	
Dielectric Strength	2000 V between winding and ground	
	4000 V between primary and secondary	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	26.000 cm
Package 1 Width	35.000 cm
Package 1 Length	35.000 cm
Package 1 Weight	15.040 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	4
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	68.660 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Mercury Free	
	Rohs Exemption Information	Yes
	Pvc Free	


Certifications & Standards

Reach Regulation	REACh Declaration		
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)		
China Rohs Regulation	China RoHS declaration		
Environmental Disclosure	Product Environmental Profile		
Circularity Profile	No need of specific recycling operations Circularity Profile		

ABL6TS100G

Dimensions Drawings

Dimensions



Dimensions in mm

а	b	С	G	J	Ø
174	163	138	135	111.5	7

Dimensions in in.


Billionolono III III.					
а	b	С	G	J	Ø
6.85	6.42	5.43	5.31	4.39	0.27

Product datasheet


ABL6TS100G


Connections and Schema

Internal Scheme



Primary Voltage Wiring





Secondary Voltage Wiring

