Product datasheet





voltage transformer - 230..400 V -1 x 115 V - 100 VA

ABL6TS10G

- ! To be discontinued on: 01-Jun-2024
- ! To be end-of-service on: 01-Jun-2025

(!) Discontinued

Main

Range Of Product	Modicon Transformer Optimized				
Product Or Component Type	Safety and isolation transformer				
Rated Power In Va	100 VA				
Input Voltage	230 V AC single phase, terminal(s): N-L1 400 V AC phase to phase, terminal(s): L1-L2				
Output Voltage	115 V AC				
Secondary Winding	Single				
Protective Cover	Without				
Ambient Air Temperature For	-2050 °C				

Complementary

Complementary					
Input Voltage Limits	360440 V 207253 V				
Network Frequency Limits	4763 Hz				
Input Voltage Tolerance	+/- 15 V				
Efficiency	86 %				
Power Dissipation In W	16.3 W				
Output Sustained Overvoltage	8 % (no load, hot state)				
Maximum Voltage Drop At Rated Load	0.6 %				
No Load Losses	7.1 W				
Short-Circuit Voltage	0,0751				
Output Protection Type	Against overload, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection				
Connections - Terminals	For input connection: screw type terminals, connection capacity: 5 x 4 mm² AWG 11 For input ground connection: screw type terminals, connection capacity: 1 x 4 mm² AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² AWG 11				
	CE				
Fixing Mode	By 4 screws diameter: 4.8 mm on vertical panel, operating position: horizontal By 4 screws diameter: 4.8 mm on vertical panel, operating position: vertical By clips (with mounting plate) on 35 mm symmetrical DIN rail				

By 4 screws diameter: 4.8 mm on horizontal panel with derating to 90 %

Life Is On Schneider 17-Apr-2024

Operating Altitude	3000 m
Electrical Insulation Class	Class B
Width	84.0 mm
Height	86.0 mm
Depth	94.0 mm
Net Weight	2.02 kg

Environment

Product Certifications	EAC UR DNV-GL			
Standards	UL 506			
Ip Degree Of Protection	IP20			
Environmental Characteristic	EMC conforming to EN 62041 Safety conforming to EN 61558-1 Safety conforming to EN 61558-2-4			
Protective Treatment	TC			
Ambient Air Temperature For Storage	-4080 °C			
Overvoltage Category	Class I conforming to VDE 0106-1			
Dielectric Strength	2000 V between winding and ground 4000 V between primary and secondary			

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	18.500 cm
Package 1 Width	12.500 cm
Package 1 Length	15.000 cm
Package 1 Weight	2.214 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	60
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	143.200 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance




Certifications & Standards


Reach Regulation	REACh Declaration				
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)				
China Rohs Regulation	China RoHS declaration				
Environmental Disclosure	Product Environmental Profile				
Circularity Profile	No need of specific recycling operations Circularity Profile				

ABL6TS10G

Dimensions Drawings

Dimensions





Dimensions in mm

а	b	С	G	J	Ø
84	94	86	64	65.5	4.8

Dimensions in in.


Dimensione in in.					
а	b	С	G	J	Ø
3.31	3.70	3.39	2.52	2.58	0.19

Product datasheet


ABL6TS10G


Connections and Schema

Internal Scheme



Primary Voltage Wiring





Secondary Voltage Wiring

