Product datasheet

Specifications





voltage transformer - 230..400 V - 1 x 115 V - 250 VA

Local distributor code: 389706355

ABL6TS25G

! To be discontinued on: 30 May 2024

! To be end-of-service on: 30 May 2025

① To be discontinued

EAN Code: 3389110598032

Main

Range Of Product	Modicon Transformer Optimized		
Product Or Component Type	Safety and isolation transformer		
Rated Power In Va	250 VA		
Input Voltage	230 V AC single phase, terminal(s): N-L1 400 V AC phase to phase, terminal(s): L1-L2		
Output Voltage	115 V AC		
Secondary Winding	Single		
Protective Cover	Without		
Ambient Air Temperature For Operation	-2050 °C		

Complementary

360440 V
207253 V
4763 Hz
+/- 15 V
90 %
27.8 W
5 % (no load, hot state)
0.7 %
12.5 W
0,0528
Against overload, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection
For input connection: screw type terminals, connection capacity: 5 x 4 mm² AWG 11 For input ground connection: screw type terminals, connection capacity: 1 x 4 mm² AWG 11 For output connection: screw type terminals, connection capacity: 2 x 4 mm² AWG 11
CE
By 4 screws diameter: 5.8 mm on vertical panel, operating position: horizontal By 4 screws diameter: 5.8 mm on vertical panel, operating position: vertical By 4 screws diameter: 5.8 mm on horizontal panel with derating to 90 %
by 4 sciews diameter. 5.5 mm of nonzontal paner with defating to 50 %

Electrical Insulation Class	Class B
Width	120.0 mm
Height	93.0 mm
Depth	122.0 mm
Net Weight	4.05 kg

Environment

Product Certifications	EAC	
	UR	
	DNV-GL	
Standards	UL 506	
Ip Degree Of Protection	IP20	
Environmental Characteristic	EMC conforming to EN 62041	
	Safety conforming to EN 61558-1	
	Safety conforming to EN 61558-2-4	
Protective Treatment	тс	
Ambient Air Temperature For Storage	-4080 °C	
Overvoltage Category	Class I conforming to VDE 0106-1	
Dielectric Strength	2000 V between winding and ground	
	4000 V between primary and secondary	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	21.500 cm
Package 1 Width	20.000 cm
Package 1 Length	23.000 cm
Package 1 Weight	4.287 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	30
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	141.610 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Mercury Free	
	Rohs Exemption Information	Yes
	Pvc Free	


Certifications & Standards

Reach Regulation	REACh Declaration		
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)		
China Rohs Regulation	China RoHS declaration		
Environmental Disclosure	Product Environmental Profile		
Circularity Profile	No need of specific recycling operations Circularity Profile		

ABL6TS25G

Dimensions Drawings

Dimensions



Dimensions in mm

а	b	С	G	J	Ø
120	122	93	90	74.5	5.8

Dimensions in in.


Difficiono in ini.					
а	b	С	G	J	Ø
4.72	4.80	3.66	3.54	2.93	0.23

Product datasheet


ABL6TS25G


Connections and Schema

Internal Scheme



Primary Voltage Wiring





Secondary Voltage Wiring

