Product data sheet

Specifications

≺Green Premium"



Regulated switch power supply, modicon power supply, 1 or 2 phase, 100...240V AC, 24V, 0.6A

ABL8MEM24006

Discontinued on: Feb 17, 2021

① Discontinued

Product availability: Stock - Normally stocked in distribution facility

Main

Range Of Product	Modicon Power Supply	
Product Or Component Type	Power supply	
Power Supply Type	Regulated switch mode	
Nominal Input Voltage	100240 V AC phase to phase L1-L2 100240 V AC single phase N-L1 120250 V DC	
Kw Rating	15 W	
Output Voltage	24 V DC	
Power Supply Output Current	0.6 A	

Complementary

Complementaly			
Efficiency At Full Load	85264 V AC		
Input Protection Type	Integrated fuse (not interchangeable)		
Inrush Current	20 A		
Power Factor	0.5 at 24 V DC		
Efficiency	80 %		
Output Voltage Adjustment	22.228.8 V adjustable		
Power Dissipation In W	3.8 W		
Current Consumption	0.25 A 240 V AC 0.4 A 100 V AC		
Residual Ripple	250 mV		
Output Protection Type	Thermal Against short-circuits		
Connections - Terminals	Screw type terminals 2 x 0.142 x 2.5 mm ² , AWG 26AWG 14) input connection Screw type terminals 2 x 0.142 x 2.5 mm ² , AWG 26AWG 14) output connection		
Status Led	1 LED (Green) output voltage		
Depth	2.32 in (59 mm)		
Height	3.94 in (100 mm)		
Width	1.42 in (36 mm)		
Net Weight	0.22 lb(US) (0.1 kg)		
Output Coupling	Parallel Series		

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Marking	CE	
Mounting Support	35 x 7.5 mm symmetrical DIN rail panel 2 screws, diameter : 4 mm 35 x 15 mm symmetrical DIN rail	
Operating Position	Vertical	
Supply	SELV EN/IEC 60950-1 SELV EN/IEC 60204-1 SELV IEC 60364-4-41	
Dielectric Strength	3000 V with between input and output	

Environment

Standards	UL 508 CSA C22.2 No 60950-1 EN/IEC 62368-1	
Product Certifications	TUV 60950-1 EAC KC RCM CCSAus CSA 22-2 No 950 CULus 508	
Environmental Characteristic	EMC EN 55022 Class B EMC EN 61000-6-3 EMC EN/IEC 61000-6-2 EMC EN/IEC 61204-3 Safety EN/IEC 60950-1	
Operating Altitude	6561.68 ft (2000 m)	
Ip Degree Of Protection	IP20 conforming to EN/IEC 60529	
Ambient Air Temperature For Operation	-13131 °F (-2555 °C) without derating mounting position A < 6561.68 ft (2000 m) 131158 °F (5570 °C) with derating factor mounting position A < 6561.68 ft (2000 m)	

Ordering and shipping details

Category	US1CP1222525
Discount Schedule	CP12
Gtin	00785901490036
Returnability	No
Country Of Origin	CN

Packing Units

-	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.97 in (5 cm)
Package 1 Width	2.87 in (7.3 cm)
Package 1 Length	3.94 in (10 cm)
Package 1 Weight	4.59 oz (130 g)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free


Certifications & Standards


Reach Regulation	REACh Declaration		
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)		
China Rohs Regulation	China RoHS declaration		
Environmental Disclosure	Product Environmental Profile		
Circularity Profile	End of Life Information		
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		

Dimensions Drawings

Regulated Switch Mode Power Supplies

Dimensions






	a in mm	a in in.	a1 in mm	a1 in in.
ABL8MEM05040	54	2.12	42	1.65
ABL8MEM12020	54	2.12	42	1.65
ABL8MEM24003	36	1.41	24	0.94
ABL8MEM24006	36	1.41	24	0.94
ABL8MEM24012	54	2.12	42	1.65
ABL7RM24025	74	2.91	60	2.36

Connections and Schema


Regulated Switch Mode Power Supply

Internal Wiring Diagram




Regulated Switch Mode Power Supplies

Series or Parallel Connection Series Connection



(1) Two Shottky diodes Imin = power supply In and Vmin = 50 V Parallel Connection



Family	Series	Parallel	
ABL 7RM/8MEM	2 products max.	2 products max.	

NOTE: Series or parallel connection is only recommended for products with identical references.

Product data sheet


ABL8MEM24006

Performance Curves

Regulated Switch Mode Power Supplies

Derating

The ambient temperature is a determining factor that limits the power an electronic power supply can deliver continuously. If the temperature around the electronic components is too high, their life will be significantly reduced. The nominal ambient temperature for the Modular range of Phaseo power supplies is 55°C. Above this temperature, derating is necessary up to a maximum temperature of 70°C (except for the ABL7RM24025 model). The graph below shows the power as a percentage of the nominal power that the power supply can deliver continuously, depending on the ambient temperature.



X Maximum operating temperature (°C) (1) With an ABL7RM24025

(2) With an ABL8MEM