Specifications

#### Green Premium<sup>™</sup>



# Regulated Power Supply, 100 to 240V AC, 24V, 20A, single phase, Optimized

ABLS1A24200

## Main

Range of product	Modicon Power Supply
Product or component type	Power supply
Power supply type	Regulated switch mode
Variant option	Optimized
Enclosure material	Aluminium
Nominal input voltage	100240 V AC single phase 100240 V AC phase to phase 140340 V DC
Rated power in W	480 W
Output voltage	24 V DC
Power supply output current	20 A

## Complementary

oompromontal y	
Input voltage limits	85264 V AC without temperature derating
	120375 V DC without temperature derating
Nominal network frequency	5060 Hz
Network system compatibility	TN
	TT
	IT
Maximum leakage current	1 mA 240 V AC
Input protection type	Integrated fuse (not interchangeable) 10 A
	External protection (recommended) 20 A Curve C
	External protection (recommended) 16 A Curve B
	External protection (recommended) 13 A Curve C
Inrush current	45.0 A at 115 V
	90.0 A at 230 V
Power factor	0.95 at 115 V AC
	0.95 at 230 V AC
Efficiency	85 % at 115 V AC
•	88 % at 230 V AC
Output voltage adjustment	2228 V
Power dissipation in W	60 W
Current consumption	< 5.4 A 115 V AC
	< 2.7 A 230 V AC
	< 5 A 140 V DC
Turn-on time	< 1.5 s
Holding time	> 20 ms 115 V AC
	> 20 ms 230 V AC

Startup with capacitive loads	8000 µF
Residual ripple	< 120 mV
Meantime between failure [MTBF]	700000 h at 25 °C, full load conforming to SR 332
Output protection type	Against overload and short-circuits, protection technology: automatic reset Against over temperature, protection technology: manual reset Against overvoltage, protection technology: manual reset
Connections - terminals	Screw connection: 0.754 mm <sup>2</sup> , (AWG 20AWG 12) without wire end ferrule for output Screw connection: 0.754 mm <sup>2</sup> , (AWG 20AWG 14) with wire end ferrule for output Screw connection: 0.754 mm <sup>2</sup> , (AWG 18AWG 12) without wire end ferrule for input Screw connection: 0.754 mm <sup>2</sup> , (AWG 18AWG 12) with wire end ferrule for input
Line and load regulation	< 0.5 % at 0 to 100 % load at 25 °C < 1 % at full voltage range in line at 25 °C
Status LED	1 LED (green) output voltage
Depth	128.5 mm
Height	123.6 mm
Width	85.5 mm
Net weight	1.25 kg
Output coupling	Parallel Serial
Mounting support	Top hat type TH35-15 rail conforming to IEC 60715 Top hat type TH35-7.5 rail conforming to IEC 60715 Double-profile DIN rail
Supply	SELV conforming to IEC 60950-1 SELV conforming to IEC 60204-1 SELV conforming to IEC 60364-4-41
Dielectric strength	3000 V AC with input to output
Service life	10 year(s)
Overvoltage category	II

## Environment

Standards	IEC 62368-1 EN/IEC 61010-1 EN 61010-2-201 EN/IEC 61204-3 IEC 61000-6-1 IEC 61000-6-2 IEC 61000-6-3 IEC 61000-6-4 IEC 61000-3-3 UL 62368-1 UL 61010-3-3 UL 62368-1 UL 61010-2-201 CSA C22.2 No 62368-1 CSA C22.2 No 61010-1 CSA C22.2 No 61010-2-201 EN/IEC 62368-1
Product certifications	CE CUL listed CUL recognized RCM CB Scheme EAC KC
Operating altitude	< 5000 m
Shock resistance	150 m/s <sup>2</sup> for 11 ms

IP degree of protection	IP20
Ambient air temperature for operation	-2040 °C without derating mounting position A 115 V AC < 2000 m -2050 °C without derating mounting position A 230 V AC < 2000 m 4070 °C with current derating of 1.67 % per °C mounting position A 115 V AC < 2000 m 5070 °C with current derating of 2.5 % per °C mounting position A 230 V AC < 2000 m
Electrical shock protection class	Class I
Pollution degree	2
Vibration resistance	3 mm (f= 29 Hz) conforming to IEC 60068-2-6 10 m/s² (f= 9200 Hz) conforming to IEC 60068-2-6
Electromagnetic immunity	Immunity to electrostatic discharge - test level: 8 kV (contact discharge) conforming to IEC 61000-4-2 Immunity to electrostatic discharge - test level: 15 kV (air discharge) conforming to IEC 61000-4-2 Immunity to conducted RF disturbances - test level: 15 V/m (80 MHz2 GHz) conforming to IEC 61000-4-3 Immunity to conducted RF disturbances - test level: 5 V/m (22.7 GHz) conforming to IEC 61000-4-3 Immunity to conducted RF disturbances - test level: 5 V/m (22.7 GHz) conforming to IEC 61000-4-3 Immunity to conducted RF disturbances - test level: 5 V/m (2.76 GHz) conforming to IEC 61000-4-3 Immunity to fast transients - test level: 4 kV (on input-output) conforming to IEC 61000-4-4 Surge immunity test - test level: 4 kV (between power supply and earth) conforming to IEC 61000-4-5 Surge immunity test - test level: 3 kV (between phases) conforming to IEC 61000-4-5 Immunity to conducted RF disturbances - test level: 15 V (0.1580 MHz) conforming to IEC 61000-4-6 Immunity to magnetic fields - test level: 30 A/m (5060 Hz) conforming to IEC 61000-4-8 Immunity to voltage dips conforming to IEC 61000-4-11 Disturbing field emission conforming to EN 55016-2-3 Limits for harmonic current emissions conforming to IEC 61000-3-2 conforming to EN 55016-1-2 conforming to EN 55016-2-1
Electromagnetic emission	Conducted emissions conforming to IEC 61000-6-3 Radiated emissions conforming to IEC 61000-6-4

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.5 cm
Package 1 Width	17.5 cm
Package 1 Length	18.0 cm
Package 1 Weight	1.419 kg
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	10.517 kg

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

## Well-being performance



Rohs Exemption Information

## **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information


#### **Dimensions Drawings**

#### **Electrical Safety**

- If the unit is use in a manner not specified by the manufacturer, the protection provided by the equipment may be impaired.
- For means of disconnection a switch or circuit breaker, located near the product, must be included in the installation. A marking as disconnecting device for the product is required.
- The device has an internal fuse. The unit is tested and approved with branch circuit protective device up to 20A. This circuit breaker can be used as disconnecting device.
- The power supply is only suitable for audio, video, information, communication, industrial and control equipment.

#### Dimensions


#### Front and Side Views



#### Connections and Schema

#### **Connections and Schema**

#### Wiring




(1) : Output wiring

(2) : Input wiring


This is only the terminal wire rating. The wire size to be used in the application must be selected by the machine builder according to the ambient temperature, the wiring method and the end-use product standard. The unit has been tested and approved with input wire  $(80^{\circ}C)$  and output wire 1 x 12AWG (95°C) or 3 x 18 AWG copper wire.

#### **Correct Parallel Connection**




(1) : Load

**Incorrect Parallel Connection** 




(1) : Load ABLx1Axxxxx-1 = ABLx1Axxxxx-2 max 2 x ABLx1Axxxxx L1 = L2 ∆V max 25 mV I<sub>Load</sub> < 90% 2 x I<sub>nom</sub>

#### **Output Voltage Balancing**



(1): R<sub>Load1</sub> (2): R<sub>Load2</sub> R<sub>Load1</sub>= R<sub>Load2</sub> I<sub>1</sub> = I<sub>2</sub> = ~ I<sub>nom</sub>

**Series Connection** 






- (2) :  $V_{out2}$
- (3) : 2 x Diode,  $V_{RRM}$  > 2 x  $V_{out1/2}$ ,  $I_F$  > 2 x  $I_{nom1/2}$
- (4) : V<sub>Load</sub> = 2 x V<sub>out</sub>
- (5) : Load


Mounting and Clearance

#### Mounting


#### **Mounting Position A**



#### **Mounting Position B**




**Incorrect Mounting** 




Performance Curves

#### Performance Curve

#### **Mounting Position A**




#### **Mounting Position B**



- X : Surrounding Air Temperature (°C)
- Y: Percentage of Maximum Load (%)
- 1 : Altitude ≤ 2000 m (6561 ft), Input voltage = 230 VAC / 325 VDC
- 2 : Altitude ≤ 2000 m (6561 ft), 115 VAC / 162 VDC
- 3 : Altitude ≤ 5000 m (16404 ft), Input voltage = 230 VAC / 325 VDC
- 4 : Altitude ≤ 5000 m (16404 ft), 115 VAC / 162 VDC

DC input voltage



X : Surrounding Air Temperature (°C)

Y: Percentage of Maximum Load (%)

1:110 VDC

2:90 VDC

3:85 VDC