Product datasheet

Specifications





voltage transformer - 230..400 V - 2 x 24 V - 40 VA

ABT7PDU004B

- () To be discontinued on: 01-Jun-2024
- () To be end-of-service on: 01-Jun-2025

① Discontinued

Main

Range Of Product	Modicon Transformer Universal			
Product Or Component Type	Safety and isolation transformer			
Rated Power In Va	40 VA			
Input Voltage	230 V AC single phase, terminal(s): N-L1 400 V AC phase to phase, terminal(s): L1-L2			
Output Voltage	24/48 V AC			
Secondary Winding	Double			
Protective Cover	With			
Ambient Air Temperature For Operation	-2060 °C			

Complementary

_					
Input Voltage Limits	207253 V				
	360440 V				
Network Frequency Limits	4763 Hz				
Input Voltage Tolerance	+/- 15 V				
Efficiency	79 %				
Power Dissipation In W 10.6 W					
Voltage Variation At Nominal Load	6.16 % at 230 V				
	6.5 % at 400 V				
Output Sustained Overvoltage	0,024 (no load, hot state)				
Maximum Voltage Drop At Rated Load	6 %				
No Load Losses	6.73 W				
Short-Circuit Voltage	0,106				
Output Protection Type	Against overload, protection technology: with additional protection fuses or circuit-				
	breakers in Selection of Protection				
	Against overvoltage, protection technology: with additional protection fuses or circuit-				
	breakers in Selection of Protection				
	Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection				
Connections - Terminals	For input connection: screw type terminals, connection capacity: 5 x 4 mm ² AWG 11				
	For input ground connection: screw type terminals, connection capacity: 1 x 4 mm ² AWG 11				
	For output connection: screw type terminals, connection capacity: 4 x 4 mm ² AWG 11				
Marking	CE				

Fixing Mode	By 4 screws diameter: 5.5 mm on vertical panel, operating position: horizontal By 4 screws diameter: 5.5 mm on vertical panel, operating position: vertical By clips on 35 x 15 mm symmetrical DIN rail By 4 screws diameter: 5.5 mm on horizontal panel with derating to 90 %					
Output Coupling	Series by internal jumper Parallel Grounding of secondary					
Operating Altitude	3000 m					
Electrical Insulation Class	Class B					
Status Led	1 LED (orange) input voltage					
Width	87.0 mm					
Height	108.0 mm					
Depth	103.0 mm					
Net Weight	1.40 kg					

Environment

Product Certifications	EAC UR DNV-GL		
Standards	UL 506		
Ip Degree Of Protection	IP20		
Environmental Characteristic	EMC conforming to EN 62041 Safety conforming to EN 61558-1 Safety conforming to EN 61558-2-6		
Ambient Air Temperature For Storage	-4080 °C		
Relative Humidity	095 % during operation		
Overvoltage Category	Class I conforming to VDE 0106-1		
Dielectric Strength	3200 V between input and ground 3200 V between output and ground 5100 V between input and output		

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	25.500 cm
Package 1 Width	18.500 cm
Package 1 Length	11.600 cm
Package 1 Weight	1.717 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	30
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	64.510 kg

Contractual warranty

Warranty

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free


Certifications & Standards


Reach Regulation	REACh Declaration				
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)				
China Rohs Regulation	China RoHS declaration				
Environmental Disclosure	Product Environmental Profile				
Circularity Profile	No need of specific recycling operations Circularity Profile				

Product datasheet

Dimensions Drawings

Dimensions





Dimensions in mm

а	b	с	G	J	Ø
87	103	108	60	96	5.5


Dimensions in in.

а	b	С	G	J	Ø
3.42	4.05	4.25	2.36	3.78	0.22


Product datasheet

Connections and Schema


Internal Scheme



Primary Voltage Wiring



Secondary Voltage Wiring



J2, J3, J4 Internal Jumper