



voltage transformer - 230..400 V - 2 x 24 V - 1 KVA

ABT7PDU100B

- Discontinued on: Aug 27, 2020
- ! To be end-of-service on: Dec 20, 2025

① Discontinued

Main

Range Of Product	Modicon Transformer Universal			
Product Or Component Type	Safety and isolation transformer			
Rated Power In Va	1000 VA			
Input Voltage	230 V AC single phase, terminal(s): N-L1 400 V AC phase to phase, terminal(s): L1-L2			
Output Voltage	24/48 V AC			
Secondary Winding	Double			
Protective Cover	Without			
Ambient Air Temperature For Operation	-2060 °C			

Complementary

Complementary	
Input Voltage Limits	207253 V 360440 V
Network Frequency Limits	4763 Hz
Input Voltage Tolerance	+/- 15 V
Efficiency	92 %
Power Dissipation In W	87 W
Voltage Variation At Nominal Load	0,0337 at 230 V 0,0362 at 400 V
Output Sustained Overvoltage	0,037 (no load, hot state)
Maximum Voltage Drop At Rated Load	4.46 %
No Load Losses	32.95 W
Short-Circuit Voltage	0,047
Output Protection Type	Against overload, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Against overvoltage, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection
Connections - Terminals	For input connection: screw type terminals, connection capacity: 5 x 4 mm² AWG 11 For input ground connection: screw type terminals, connection capacity: 1 x 4 mm² AWG 11 For output connection: screw type terminals, connection capacity: 4 x 10 mm² AWG 6
Marking	CE

Fixing Mode	By 4 screws diameter: 7 mm on vertical panel, operating position: horizontal By 4 screws diameter: 7 mm on vertical panel, operating position: vertical By 4 screws diameter: 7 mm on horizontal panel with derating to 90 %			
Output Coupling	Series by internal jumper Parallel Grounding of secondary			
Operating Altitude	3000 m			
Electrical Insulation Class	Class F			
Width	150.0 mm			
Height	156.0 mm			
Depth	196.0 mm			
Net Weight	13.69 kg			

Environment

Product Certifications	EAC UR DNV-GL	
Standards	UL 506	
Ip Degree Of Protection	IP20	
Environmental Characteristic	EMC conforming to EN 62041 Safety conforming to EN 61558-1 Safety conforming to EN 61558-2-6	
Ambient Air Temperature For Storage	-4080 °C	
Relative Humidity	095 % during operation	
Overvoltage Category	Class I conforming to VDE 0106-1	
Dielectric Strength	3200 V between input and ground 3200 V between output and ground 5100 V between input and output	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	25.500 cm
Package 1 Width	34.500 cm
Package 1 Length	35.200 cm
Package 1 Weight	14.824 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	4
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	67.796 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >


Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance




Certifications & Standards

Reach Regulation	REACh Declaration			
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)			
China Rohs Regulation	China RoHS declaration			
Environmental Disclosure	Product Environmental Profile			
Circularity Profile	No need of specific recycling operations Circularity Profile			

ABT7PDU100B

Dimensions Drawings

Dimensions



Dimensions in mm

а	b	С	G	J	Ø
150	196	156	122	134	7

Dimensions in in.


а	b	С	G	J	Ø
5.90	7.72	6.14	4.80	5.28	0.27

Product datasheet


ABT7PDU100B


Connections and Schema

Internal Scheme




Primary Voltage Wiring





Secondary Voltage Wiring



J2, J3, J4 Internal Jumper