



 PRODUCT-DETAILS

AF210-30-11-70

AF210-30-11 100-250V 50/60Hz / 100-250V DC Contactor

"No longer for sale" replaced by



General Information

| | |
|-----------------------|--|
| Extended Product Type | AF210-30-11-70 |
| Product ID | 1SFL517001R7011 |
| EAN | 7320500220276 |
| Catalog Description | AF210-30-11 100-250V 50/60Hz / 100-250V DC Contactor |
| Long Description | A 3-phase Contactor suitable for various applications such as Motor starting, Isolation, By-pass and Distribution application up to max 690 V. Operated with wide control voltage range 100-250 V, AC/DC |

Ordering

| | |
|------------------------------|-----------------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85364900 |
| Replacement Product ID (NEW) | 1SFL527002R1311 |

Popular Downloads

| | |
|-----------------------|-----------------|
| Data Sheet, Technical | 1SBC100192C0206 |
|-----------------------|-----------------|

Information

| | |
|--------------------------|---------------|
| Instructions and Manuals | 1SFC380003-89 |
| Dimension Diagram | 53540930-2 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 140 mm |
| Product Net Depth / Length | 180.5 mm |
| Product Net Height | 227 mm |
| Product Net Weight | 5.05 kg |

Technical

| | |
|---|--|
| Number of Main Contacts NO | 3 |
| Number of Main Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 1 |
| Number of Auxiliary Contacts NC | 1 |
| Rated Operational Voltage | Main Circuit 690 V |
| Rated Frequency (f) | Main Circuit 50 / 60 Hz |
| Conventional Free-air Thermal Current (I _{th}) | acc. to IEC 60947-4-1, Open Contactors Θ = 40 °C 350 A |
| Rated Operational Current AC-1 (I _e) | (690 V) 40 °C 350 A (690 V) 55 °C 300 A (690 V) 70 °C 240 A |
| Rated Operational Current AC-3 (I _e) | (415 V) 55 °C 210 A (440 V) 55 °C 210 A (500 V) 55 °C 210 A (690 V) 55 °C 210 A (380 / 400 V) 55 °C 210 A (220 / 230 / 240 V) 55 °C 210 |
| Rated Operational Power AC-3 (P _e) | (415 V) 110 kW (440 V) 110 kW (500 V) 132 kW (690 V) 160 kW (380 / 400 V) 110 kW (220 / 230 / 240 V) 59 kW |
| Rated Breaking Capacity AC-3 | 8 x I _e AC-3 |
| Rated Making Capacity AC-3 | 10 x I _e AC-3 |
| Short-Circuit Protective Devices | gG Type Fuses 400 A |
| Rated Short-time Withstand Current Low Voltage (I _{cw}) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 1700 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 400 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 1000 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 2500 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 1200 A |
| Maximum Breaking Capacity | cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 2200 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 2000 A |
| Maximum Electrical Switching Frequency | (AC-1) 300 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 300 cycles per hour |
| Rated Operational Current DC-1 (I _e) | (110 V) 2 Poles in Series, 40 °C 350 A (220 V) 3 Poles in Series, 40 °C 350 A |

| | |
|---|--|
| Rated Operational Current DC-3 (I _e) | (110 V) 2 Poles in Series, 40 °C 350 A (220 V) 3 Poles in Series, 40 °C 350 A |
| Rated Operational Current DC-5 (I _e) | (110 V) 2 Poles in Series, 40 °C 350 A (220 V) 3 Poles in Series, 40 °C 350 A |
| Rated Insulation Voltage (U _i) | acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V |
| Rated Impulse Withstand Voltage (U _{imp}) | Main Circuit 8 kV |
| Mechanical Durability | 5 million |
| Maximum Mechanical Switching Frequency | 300 cycles per hour |
| Coil Operating Limits | (acc. to IEC 60947-4-1) 0.85 x U _c Min. ... 1.1 x U _c Max. (at θ ≤ 70 °C) |
| Rated Control Circuit Voltage (U _c) | 50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V |
| Coil Consumption | Holding at Max. Rated Control Circuit Voltage 50 Hz 10 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 10 V·A Holding at Max. Rated Control Circuit Voltage DC 2 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 470 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 470 V·A Pull-in at Max. Rated Control Circuit Voltage DC 520 W |
| Operate Time | Between Coil De-energization and NC Contact Closing 40 ... 50 ms Between Coil De-energization and NO Contact Opening 43 ... 53 ms Between Coil Energization and NC Contact Opening 45 ... 85 ms Between Coil Energization and NO Contact Closing 50 ... 90 ms |
| Connecting Capacity Main Circuit | Bar 32 mm ² Rigid Al-Cable 2 x 95 ... 120 mm ² Rigid Cu-Cable 16 ... 240 mm ² |
| Connecting Capacity Auxiliary Circuit | Flexible with Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible 2x0.75 ... 2.5 mm ² Solid 2 x 1 ... 4 mm ² Stranded 2 x 1 ... 4 mm ² |
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00 |
| Terminal Type | Main Circuit: Bars |

Technical UL/CSA

| | |
|----------------------------------|--|
| Maximum Operating Voltage UL/CSA | Main Circuit 600 V |
| General Use Rating UL/CSA | (600 V AC) 300 A |
| Horsepower Rating UL/CSA | (200 V AC) Three Phase 60 hp (208 V AC) Three Phase 60 hp (220 ... 240 V AC) Three Phase 75 hp (440 ... 480 V AC) Three Phase 150 hp (550 ... 600 V AC) Three Phase 200 hp |

Environmental

| | |
|--|--|
| Ambient Air Temperature | Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 U _c) -25 ... 50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 U _c) -40 ... 70 °C Close to Contactor for Storage -40 ... 70 °C |
| Maximum Operating Altitude Permissible | Without Derating 3000 m |
| Resistance to Shock acc. to IEC 60068-2-27 | Shock Direction: A 5 g Shock Direction: B1 5 g Shock Direction: B2 5 g Shock Direction: C1 5 g |

Shock Direction: C2 5 g

Material Compliance

| | |
|------------------|--|
| RoHS Information | 2CMT2015-005436 |
| RoHS Status | Following EU Directive 2011/65/EU |
| WEEE B2C / B2B | Business To Business |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Certificates and Declarations

| | |
|---------------------------------|---------------------|
| ABS Certificate | 15-LD1408622-PDA |
| BV Certificate | BV_13409-COBV |
| CB Certificate | SEMKO_SE-69491A1 |
| CCS Certificate | GB14T00030 |
| CQC Certificate | CQC2007010304256681 |
| Declaration of Conformity - CCC | 2020980304001554 |
| Declaration of Conformity - CE | 2CMT2015-005436 |
| DNV GL Certificate | TAE00001W1 |
| EAC Certificate | 9AKK107046A8618 |
| GL Certificate | GL_20262-04HH |
| LOVAG Certificate | SE-0115198 |
| LR Certificate | 16-20064 |
| RINA Certificate | ELE060313XG_002 |
| RMRS Certificate | RMRS_12-03683-315 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 203 mm |
| Package Level 1 Depth / Length | 245 mm |
| Package Level 1 Height | 188 mm |
| Package Level 1 Gross Weight | 5.75 kg |
| Package Level 1 EAN | 7320500220276 |

Classifications

| | |
|------------------------------------|--|
| Object Classification Code | Q |
| ETIM 7 | EC000066 - Power contactor, AC switching |
| ETIM 8 | EC000066 - Power contactor, AC switching |
| ETIM 9 | EC000066 - Power contactor, AC switching |
| eClass | V11.0 : 27371003 |
| UNSPSC | 39121529 |
| IDEA Granular Category Code (IGCC) | 4755 >> Contactors |
| E-Number (Finland) | 3709247 |
| E-Number (Norway) | 4115275 |
| E-Number (Sweden) | 3228306 |

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors

