

**NZM2 PXR10 circuit breaker, 3 pole, 160A, screw terminal**

Part no. **NZMN2-AX160**
192004

EL Number **4362850**
(Norway)

General specifications

Product name	Eaton Moeller series NZM molded case circuit breaker electronic
Part no.	NZMN2-AX160
EAN	4015081925551
Product Length/Depth	190 millimetre
Product height	160 millimetre
Product width	115 millimetre
Product weight	2.3 kilogram
Compliances	RoHS conform
Certifications	IEC IEC/EN 60947
Product Tradename	NZM
Product Type	Molded case circuit breaker
Product Sub Type	Electronic

Delivery program

Application	Use in unearthed supply systems at 690 V
Type	Circuit breaker
Circuit breaker frame type	NZM2
Number of poles	Three-pole
Amperage Rating	160 A
Release system	Electronic release
Features	Motor drive optional Protection unit
Special features	Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn) Overload and short-circuit protection LI R.m.s. value measurement and "thermal memory" USB interface for configuration and test function with Power Xpert Protection Manager software Rated current = rated uninterrupted current: 160 A

Technical Data - Electrical

Voltage rating	690 V - 690 V
Rated insulation voltage (Ui)	690 V AC
Rated impulse withstand voltage (Uimp) at auxiliary contacts	6000 V
Rated impulse withstand voltage (Uimp) at main contacts	8000 V
Rated short-time withstand current (t = 0.3 s)	1.9 kA
Rated short-time withstand current (t = 1 s)	1.9 kA
Instantaneous current setting (Ii) - min	2 A
Instantaneous current setting (Ii) - max	12 A
Overload current setting (Ir) - min	64 A
Overload current setting (Ir) - max	160 A
Short delay current setting (Isd) - min	0 A
Short delay current setting (Isd) - max	0 A
Short-circuit release non-delayed setting - min	320 A
Short-circuit release non-delayed setting - max	1920 A
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 230 V, 50/60 Hz	85 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz	50 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 440 V, 50/60 Hz	35 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 525 V, 50/60 Hz	25 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz	5 kA

Rated short-circuit making capacity I _{cm} at 240 V, 50/60 Hz			187 kA
Rated short-circuit making capacity I _{cm} at 400/415 V, 50/60 Hz			105 kA
Rated short-circuit making capacity I _{cm} at 440 V, 50/60 Hz			74 kA
Rated short-circuit making capacity I _{cm} at 525 V, 50/60 Hz			53 kA
Rated short-circuit making capacity I _{cm} at 690 V, 50/60 Hz			40 kA
Short-circuit total breaktime			< 10 ms
Electrical connection type of main circuit			Screw connection
Isolation			500 V AC (between auxiliary contacts and main contacts) 300 V AC (between the auxiliary contacts)
Number of operations per hour - max			120
Handle type			Rocker lever
Utilization category			A (IEC/EN 60947-2)
Overvoltage category			III
Pollution degree			3
Lifespan, electrical			10000 operations at 415 V AC-1 10000 operations at 400 V AC-1 7500 operations at 690 V AC-1
Direction of incoming supply			As required
Technical Data - Mechanical			
Mounting Method			DIN rail (top hat rail) mounting optional Fixed Built-in device fixed built-in technique
Degree of protection			IP20 (basic degree of protection, in the operating controls area) IP20
Degree of protection (IP), front side			IP66 (with door coupling rotary handle) IP40 (with insulating surround)
Degree of protection (terminations)			IP00 (terminations, phase isolator and strip terminal) IP10 (tunnel terminal)
Protection against direct contact			Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110
Shock resistance			20 g (half-sinusoidal shock 20 ms)
Number of auxiliary contacts (change-over contacts)			0
Number of auxiliary contacts (normally closed contacts)			0
Number of auxiliary contacts (normally open contacts)			0
Position of connection for main current circuit			Front side
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Special features			Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I _{cn}) Overload and short-circuit protection LI R.m.s. value measurement and "thermal memory" USB interface for configuration and test function with Power Xpert Protection Manager software Rated current = rated uninterrupted current: 160 A
Lifespan, mechanical			20000 operations
Technical Data - Mechanical - Terminals			
Standard terminals			Screw terminal
Optional terminals			Box terminal. Connection on rear. Tunnel terminal
Terminal capacity (control cable)			0.75 mm ² - 2.5 mm ² (1x) 0.75 mm ² - 1.5 mm ² (2x)
Terminal capacity (aluminum solid conductor/cable)			16 mm ² (1x) at tunnel terminal
Terminal capacity (aluminum stranded conductor/cable)			25 mm ² - 185 mm ² (1x) at tunnel terminal
Terminal capacity (copper busbar)			Min. 16 mm x 5 mm direct at switch rear-side connection Max. 24 mm x 8 mm direct at switch rear-side connection M8 at rear-side screw connection
Terminal capacity (copper solid conductor/cable)			6 mm ² - 16 mm ² (2x) direct at switch rear-side connection 10 mm ² - 16 mm ² (1x) direct at switch rear-side connection 6 mm ² - 16 mm ² (2x) at box terminal 16 mm ² (1x) at tunnel terminal 10 mm ² - 16 mm ² (1x) at box terminal
Terminal capacity (copper stranded conductor/cable)			25 mm ² - 70 mm ² (2x) at box terminal 25 mm ² - 185 mm ² (1x) direct at switch rear-side connection 25 mm ² - 185 mm ² (1x) at box terminal 25 mm ² - 70 mm ² (2x) direct at switch rear-side connection 25 mm ² - 185 mm ² (1x) at 1-hole tunnel terminal
Terminal capacity (copper strip)			Max. 10 segments of 24 mm x 0.8 mm at rear-side connection (punched) Min. 2 segments of 16 mm x 0.8 mm at rear-side connection (punched)

			Max. 8 segments of 24 mm x 1 mm (2x) at box terminal Max. 10 segments of 16 mm x 0.8 mm at box terminal Min. 2 segments of 9 mm x 0.8 mm at box terminal
Design verification as per IEC/EN 61439 - technical data			
Rated operational current for specified heat dissipation (In)			160 A
Equipment heat dissipation, current-dependent			21.12 W
Ambient operating temperature - min			-25 °C
Ambient operating temperature - max			70 °C
Ambient storage temperature - min			40 °C
Ambient storage temperature - max			70 °C
Design verification as per IEC/EN 61439			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information			
Functions			System and cable protection

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecI@ss13-27-37-04-09 [AJZ716018])			
Rated permanent current Iu	A		160
Rated voltage	V		690 - 690
Rated short-circuit breaking capacity Icu at 400 V, 50 Hz	kA		50
Overload release current setting	A		64 - 160
Adjustment range short-term delayed short-circuit release	A		0 - 0
Adjustment range undelayed short-circuit release	A		2 - 12
Power loss	W		
Device construction			Built-in device fixed built-in technique
Integrated earth fault protection			No
Type of electrical connection of main circuit			Screw connection
Suitable for DIN rail (top hat rail) mounting			No
DIN rail (top hat rail) mounting optional			Yes
Number of auxiliary contacts as normally closed contact			0
Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as change-over contact			0

With switched-off indicator		No
With integrated under voltage release		No
Number of poles		3
Position of connection for main current circuit		Front side
Type of control element		Rocker lever
Complete device with protection unit		Yes
Motor drive integrated		No
Motor drive optional		Yes
Degree of protection (IP)		IP20