

Product datasheet

Specifications



switch disconnecter ComPacT NSX100NA, 4 poles, 100 A, AC22A, AC23A

C104100S

EAN Code: 3606481999283

Main

Range	ComPacT new generation
Product name	ComPacT NSX new generation
Device short name	NSX100NA
Product or component type	Switch disconnecter
Device application	Distribution
poles description	4P
[I _{th}] conventional free air thermal current	100 A at 50 °C
[I _e] rated operational current	AC-22A: 100 A AC 50/60 Hz 220...690 V AC-23A: 100 A AC 50/60 Hz 220...690 V DC-22A: 100 A DC 250 V 1 pole DC-22A: 100 A DC 500 V 2 poles in series DC-23A: 100 A DC 250 V 1 pole DC-23A: 100 A DC 500 V 2 poles in series DC-22A: 100 A DC 750 V 3 poles in series DC-23A: 100 A DC 750 V 3 poles in series
[U _e] rated operational voltage	690 V AC 50/60 Hz 750 V DC 3 poles in series 500 V DC 2 poles in series 250 V DC 1 pole
Network type	AC DC
Suitability for isolation	Yes conforming to EN/IEC 60947-3
Utilisation category	AC-22A AC-23A DC-22A DC-23A
Breaking capacity code	NA
Contact position indicator	Yes
Visible break	No
Mounting mode	Fixed
[I _{cw}] rated short-time withstand current	1.8 kA during 1 s 1.8 kA during 3 s 0.69 kA during 20 s
[I _{cm}] rated short-circuit making capacity	330 kA with upstream protection circuit breaker 2.6 kA switch-disconnector alone
Control type	Toggle
[U _i] rated insulation voltage	800 V AC 50/60 Hz
[U _{imp}] rated impulse withstand voltage	8 kV

Complementary

Mounting support	Backplate
Upside connection	Front
downside connection	Front
Connection pitch	35 mm
Mechanical durability	50000 cycles
Electrical durability	AC-22A: 35000 cycles 440 V AC 50/60 Hz In/2 AC-23A: 35000 cycles 440 V AC 50/60 Hz In/2 AC-22A: 20000 cycles 440 V AC 50/60 Hz In AC-23A: 20000 cycles 440 V AC 50/60 Hz In AC-22A: 15000 cycles 690 V AC 50/60 Hz In/2 AC-23A: 15000 cycles 690 V AC 50/60 Hz In/2 AC-22A: 8000 cycles 690 V AC 50/60 Hz In AC-23A: 8000 cycles 690 V AC 50/60 Hz In DC-22A: 10000 cycles 250 V DC In/2 (1 pole) DC-23A: 10000 cycles 250 V DC In/2 (1 pole) DC-22A: 5000 cycles 500 V DC In (2 poles in series) DC-23A: 5000 cycles 500 V DC In (2 poles in series)
Width (W)	140 mm
Height (H)	161 mm
Depth (D)	86 mm
Net weight	2.2 kg
Standards	EN/IEC 60947-1 EN/IEC 60947-3

Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Electrical shock protection class	Class II
Pollution degree	3 conforming to IEC 60664-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.0 cm
Package 1 Width	14.4 cm
Package 1 Length	19.0 cm
Package 1 Weight	2.304 kg
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	14.214 kg

Contractual warranty

Warranty

18 months

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

Pvc Free

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)