Product datasheet

Specifications

Green Premium[™]



Circuit breaker, ComPacT NSXm 160E, 16kA/415VAC, 4 poles 3D (neutral not protected), TMD trip unit 80A, lugs/busbars

C11E6TM080B

Main

Range	ComPacT new generation	
Product Name	ComPacT NSXm new generation	
Range Of Product	ComPacT NSXm new generation	
Device Short Name	NSXm 160E	
Product Or Component Type	Circuit breaker	
Device Application	Distribution	
Poles Description	4P	
Protected Poles Description	3D	
Neutral Position	Left	
[In] Rated Current	80 A at 40 °C	
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz	
Network Type	AC	
Network Frequency	50/60 Hz	
Suitability For Isolation	Yes conforming to IEC 60947-2	
Utilisation Category	Category A	
[Icu] Rated Ultimate Short-Circuit Breaking Capacity	25 kA lcu at 220240 V AC 50/60 Hz conforming to IEC 60947-2 16 kA lcu at 380415 V AC 50/60 Hz conforming to IEC 60947-2 10 kA lcu at 440 V AC 50/60 Hz conforming to IEC 60947-2 8 kA lcu at 500 V AC 50/60 Hz conforming to IEC 60947-2	
Performance Level	E 16 kA 415 V AC	
Trip Unit Name	TM-D	
Trip Unit Technology	Thermal-magnetic	
Trip Unit Protection Functions	LI	
Control Type	Toggle	
Circuit Breaker Mounting Mode	Fixed	

Complementary

[Ui] Rated Insulation Voltage	800 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ics] Rated Service Short-Circuit Breaking Capacity	25 kA at 220240 V AC 50/60 Hz conforming to IEC 60947-2 16 kA at 380415 V AC 50/60 Hz conforming to IEC 60947-2 10 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 8 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2
Mechanical Durability	20000 cycles

Electrical Durability	20000 cycles at 440 V ln/2 10000 cycles at 440 V ln 10000 cycles at 690 V ln/2 5000 cycles at 690 V ln	
Power Dissipation Per Pole	6.96 W	
Mounting Support	Backplate	
Mounting Position	Horizontal and vertical Flat on the back	
Upside Connection	Front	
Downside Connection	Front	
Connection Terminals	compression lug/busbar	
Connection Pitch	35 mm with spreaders 27 mm without spreaders	
9 Mm Pitches	12 module	
Trip Unit Rating	80 A at 40 °C	
Long-Time Pick-Up Adjustment Type Ir (Thermal Protection)	Adjustable	
[Ir] Long-Time Protection Pick-Up Adjustment Range	0.71 x ln	
Long-Time Protection Delay Adjustment Type Tr	Fixed	
Neutral Protection Settings	No protection (3D)	
Instantaneous Protection Pick-Up Adjustment Type li	Fixed	
[li] Instantaneous Protection Pick- Up Adjustment Range	1000 A	
Earth-Leakage Protection	Without	
Number Of Slots For Electrical Auxiliaries	1 slot(s) for auxiliary switch OF 1 slot(s) for alarm switch SD 1 slot(s) for voltage release MN or MX	
Local Signalling	Flag (green) for presence of auxiliary contacts	
Width (W)	108 mm	
Height (H)	137 mm	
Depth (D)	80 mm	
Net Weight	1.42 kg	
Colour	Grey (RAL 7016)	

Environment

Standards	EN/IEC 60947	
Pollution Degree	3 conforming to IEC 60664-1	
p Degree Of Protection	IP40 conforming to IEC 60529	
Ik Degree Of Protection	IK07 conforming to IEC 62262	
Ambient Air Temperature For Operation	-2570 °C	
Ambient Air Temperature For Storage	-5085 °C	
Relative Humidity	095 %	
Operating Altitude	2000 m without derating 5000 m with derating	

Packing Units

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	12.000 cm	
Package 1 Width	13.000 cm	
Package 1 Length	22.000 cm	
Package 1 Weight	1.572 kg	
Unit Type Of Package 2	S03	
Number Of Units In Package 2	6	
Package 2 Height	30.000 cm	
Package 2 Width	30.000 cm	
Package 2 Length	40.000 cm	
Package 2 Weight	10.190 kg	
Unit Type Of Package 3	P12	
Number Of Units In Package 3	144	
Package 3 Height	150.000 cm	
Package 3 Width	Width 80.000 cm	
Package 3 Length	120.000 cm	
Package 3 Weight	254.490 kg	

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.





RoHS/REACh

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Halogen Free Plastic Parts Product	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information
Circularity Profile	No need of specific recycling operations