# **Product datasheet**

Specifications





## TeSys D control relay - 3 NO + 2 NC - <= 690 V - 24 V DC low consumption coil

CAD323BL

#### Main

Range	TeSys TeSys Deca
Product Name	TeSys CAD
Product Or Component Type	Control relay
Device Short Name	CAD
Contactor Application	Control circuit

#### Complementary

Complementary	
Utilisation Category	AC-14 DC-13 AC-15
Pole Contact Composition	3 NO + 2 NC
[Ue] Rated Operational Voltage	<= 690 V AC 25400 Hz
Control Circuit Type	DC low consumption
[Uc] Control Circuit Voltage	24 V DC
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947
[Ith] Conventional Free Air Thermal Current	10 A (at 60 °C)
Irms Rated Making Capacity	140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1
[Icw] Rated Short-Time Withstand Current	100 A - 1 s 120 A - 500 ms 140 A - 100 ms
Associated Fuse Rating	10 A gG conforming to IEC 60947-5-1
[Ui] Rated Insulation Voltage	600 V UL certified 600 V CSA certified 690 V conforming to IEC 60947-5-1
Mounting Support	Plate Rail
Connections - Terminals	Spring terminals 1 cable(s) 12.5 mm²flexible without cable end Spring terminals 2 cable(s) 12.5 mm²flexible without cable end Spring terminals 1 cable(s) 12.5 mm²solid without cable end Spring terminals 2 cable(s) 12.5 mm²solid without cable end
Control Circuit Voltage Limits	0.10.25 Uc (-4070 °C):drop-out DC 0.71.25 Uc (-4060 °C):operational DC 11.25 Uc (6070 °C):operational DC
Operating Time	6588 ms coil energisation and NO closing 1425 ms coil de-energisation and NO opening 5777 ms coil energisation and NC opening 2842 ms coil de-energisation and NC closing

Mechanical Durability	30 Mcycles
Maximum Operating Rate	180 cyc/mn
Time Constant	40 ms
Inrush Power In W	2.4 W (at 20 °C)
Hold-In Power Consumption In W	2.4 W at 20 °C
Minimum Switching Voltage	17 V
Minimum Switching Current	5 mA
Non-Overlap Time	1.5 ms on energisation between NC and NO contact 1.5 ms on de-energisation between NC and NO contact
Insulation Resistance	> 10 MOhm
Mechanical Robustness	Shocks control relay open: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks control relay closed: 15 Gn for 11 ms conforming to IEC 60068-2-27 Vibrations control relay open: 2 Gn, 5300 Hz conforming to IEC 60068-2-6 Vibrations control relay closed: 4 Gn, 5300 Hz conforming to IEC 60068-2-6
Height	99 mm
Width	45 mm
Depth	93 mm
Net Weight	0.58 kg

### Environment

Standards	EN/IEC 60947-5-1 GB/T 14048.5 UL 60947-5-1 CSA C22.2 No 60947-5-1 JIS C8201-5-1
Product Certifications	CB CCC UL CSA EAC CE UKCA
Ip Degree Of Protection	IP2X conforming to VDE 0106
Protective Treatment	TH conforming to IEC 60068
Ambient Air Temperature For Operation	-4060 °C 6070 °C with derating
Ambient Air Temperature For Storage	-6080 °C
Operating Altitude	03000 m

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.700 cm
Package 1 Width	11.000 cm
Package 1 Length	12.400 cm
Package 1 Weight	544.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	15

Package 2 Height15.000 cmPackage 2 Width30.000 cmPackage 2 Length40.000 cmPackage 2 Weight8.740 kgUnit Type Of Package 3P06Number Of Units In Package 3240Package 3 Height75.000 cmPackage 3 Width60.000 cmPackage 3 Length80.000 cm	
Package 2 Length40.000 cmPackage 2 Weight8.740 kgUnit Type Of Package 3P06Number Of Units In Package 3240Package 3 Height75.000 cmPackage 3 Width60.000 cm	
Package 2 Weight 8.740 kg   Unit Type Of Package 3 P06   Number Of Units In Package 3 240   Package 3 Height 75.000 cm   Package 3 Width 60.000 cm	
Unit Type Of Package 3 P06   Number Of Units In Package 3 240   Package 3 Height 75.000 cm   Package 3 Width 60.000 cm	
Number Of Units In Package 3 240   Package 3 Height 75.000 cm   Package 3 Width 60.000 cm	
Package 3 Height 75.000 cm   Package 3 Width 60.000 cm	
Package 3 Width 60.000 cm	
-	
Package 3 Length 80.000 cm	
Package 3 Weight 148.352 kg	

## **Contractual warranty**

Warranty

18 months

### Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free

Rohs Exemption Information

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information