Product datasheet

Specifications





EasyPact TVS control relay - 2 NO + 2 NC <= 690 V - 24 VAC

CAE22B5

Main

Range	Easy TeSys
Range Of Product	Easy TeSys Control Relay
Product Or Component Type	Control relay
Device Short Name	CAE
Contactor Application	Control circuit
Colour	Grey (RAL 7011)

Complementary

Complementary	
Utilisation Category	AC-15 AC-14
Pole Contact Composition	2 NO + 2 NC
[Ue] Rated Operational Voltage	<= 690 V AC
Control Circuit Type	AC at 50 Hz
[Uc] Control Circuit Voltage	24 V AC 50 Hz
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947
[Ith] Conventional Free Air Thermal Current	10 A (at 40 °C)
Irms Rated Making Capacity	140 A at 690 V AC conforming to IEC 60947-5-1
[Icw] Rated Short-Time Withstand Current	120 A - 500 ms 140 A - 100 ms
Associated Fuse Rating	10 A gG at 690 V conforming to IEC 60947-5-1
[Ui] Rated Insulation Voltage	690 V conforming to IEC 60947-5-1
Mounting Support	Rail Plate
Connections - Terminals	Screw clamp terminals 1 12.5 mm ² - cable stiffness: flexible without cable end Screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible without cable end Screw clamp terminals 1 12.5 mm ² - cable stiffness: flexible with cable end Screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible with cable end Screw clamp terminals 1 12.5 mm ² - cable stiffness: solid without cable end Screw clamp terminals 1 12.5 mm ² - cable stiffness: solid without cable end Screw clamp terminals 2 12.5 mm ² - cable stiffness: solid without cable end
Recommended Tightening Torque	1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2
Control Circuit Voltage Limits	Operational: 0.851.1 Uc at 50 Hz Drop-out: 0.30.6 Uc
Operating Time	 419 ms coil energisation and NC opening 1222 ms coil energisation and NO closing 412 ms coil de-energisation and NC opening 617 ms coil de-energisation and NO closing
Mechanical Durability	10 Mcycles

Maximum Operating Rate	180 cyc/mn	
Inrush Power In Va	70 VA 50 Hz (at 20 °C)	
Hold-In Power Consumption In Va	8 VA 50 Hz (at 20 °C)	
Minimum Switching Voltage	17 V	
Minimum Switching Current	5 mA	
Non-Overlap Time	1.5 ms on energisation between NC and NO contact1.5 ms on de-energisation between NC and NO contact	
Insulation Resistance	> 10 MOhm	
Mechanical Robustness	Shocks control relay open: 7 Gn for 11 ms Shocks control relay closed: 10 Gn for 11 ms Vibrations control relay open: 1.5 Gn, 5300 Hz Vibrations control relay closed: 3 Gn, 5300 Hz	
Height	74 mm	
Width	45 mm	
Depth	80 mm	
Net Weight	0.28 kg	

Environment

Standards	IEC 60947-5-1
Product Certifications	GOST
Ip Degree Of Protection	IP2X conforming to IEC 60529
Protective Treatment	TH conforming to IEC 60068
Ambient Air Temperature For Operation	-2070 °C
Ambient Air Temperature For Storage	-6080 °C
Operating Altitude	3000 m without derating

Packing Units

Package 3 Length
 Package 3 Weight

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information