

Mini circuit breaker, Homeline Canadian, 40A, 2 pole, 120/240VAC, 10kA AIR, ground fault class A, plug in, UL

CHOM240GFI

Main

Range of product	Homeline
Product or component type	Miniature circuit-breaker
[In] rated current	40 A
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Plug-on
Poles description	2P
Short-circuit current	10 kA
Circuit breaker type	Ground fault protecting class A 6 mA
Circuit breaker application	HACR rated
Electrical connection	Screw clamp terminals

Complementary

Number of spaces required	2
AWG gauge	AWG 12AWG 4 aluminum/copper

Environment

Product certifications	CSA
ambient air temperature for operation	104 °F (40 °C)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.10 in (5.334 cm)
Package 1 Width	3.60 in (9.144 cm)
Package 1 Length	5.40 in (13.716 cm)
Package 1 Weight	19.360 oz (548.847 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	33
Package 2 Height	5.50 in (13.97 cm)
Package 2 Width	13.70 in (34.798 cm)
Package 2 Length	20.90 in (53.086 cm)
Package 2 Weight	40.199 lb(US) (18.234 kg)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No	
Packaging without single use plastic	Yes	
EU RoHS Directive	Compliant with Exemptions	
China RoHS Regulation	China RoHS declaration	

Use Again

○ Repack and remanufacture		
Circularity Profile	End of Life Information	
Halogen content performance	Halogen free product	
Take-back	No	