Product datasheet





Clipsal X - Foot light with LED -White

CPXFTLP2M_WE

Main

Range	Clipsal
Range Of Product	Clipsal X
Product Or Component Type	Lamp
Local Signalling	Indicator light LED
Rated Current	100 mA at 240 V AC
Cover Frame Colour Tint	White

Complementary

Wiring Device Mounting	Flush
Material	PC: top PA (polyamide) 6: bottom
Connections - Terminals	Screwless type terminals
Width	43 mm
Height	51 mm
Depth	61 mm
Resistance To Chemical Agents	Not resistant to alcohols Not resistant to cleaning agent Not resistant to thinner

Environment

Ambient Air Temperature For Operation	-535 °C
Relative Humidity	095 %

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.3 cm
Package 1 Width	5.2 cm
Package 1 Length	6.5 cm
Package 1 Weight	30.0 g
Unit Type Of Package 2	CAR
Number Of Units In Package 2	5
Package 2 Height	7.0 cm

Package 2 Width	6.0 cm
Package 2 Length	23.5 cm
Package 2 Weight	250.0 g



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations