

Search Automation Controls 🔍

- Home
- Products
- Download
- Resource
- Support
- Sales Locations

Panasonic Industry > Automation Controls Top > FA Sensors & Components > Sensors > Photoelectric Sensors / Laser Sensors > CX-423-P

Sensors

Photoelectric Sensors / Laser Sensors >

Compact Photoelectric Sensor CX-400 Ver.2 >

CX-423-P

Fiber Sensors >

Light Curtains / Safety Components >

Area Sensors >

Micro Photoelectric Sensors >

Inductive Proximity Sensors >

Particular Use Sensors >

Sensor Options >

Wire-Saving Systems >

Configuration examples of IO-Link compatible devices >

CX-423-P | Compact Photoelectric Sensor CX-400 Ver.2



*Photo may vary from actual product.



Product Number	CX-423-P
Part Number	CX-423-P
Product	Compact Photoelectric Sensor



Contact Us

Technical Inquiries,
Purchase Support &
Additional Assistance

Technical inquiry

Business inquiry

Other inquiry

Details

Diffuse reflective(Narrow-view)

Download

Catalog/
Datasheet

CAD

Manual

Contact Us

Technical inquiry

Business inquiry

Other inquiry

Spec
Detail

Accessories
(Option)

As of April 26, 2025 (JST)
*Specifications and design of the products are subject to change without notice for the product improvement.

Spec Detail

Specifications and design of the products are subject to change without notice for the product improvement.

Item	Specifications
Product Number	CX-423-P
Part Number	CX-423-P
Products Name	Compact Photoelectric Sensor
Product details	Diffuse reflective(Narrow- view)
The price of the product	Please contact our office



Item		Specifications
		Download
Catalog/ Datasheet	CAD	Manual
Applicable regulations and certifications		marking (EMC Regulations, RoHS Regulations), UL Recognition Certification
Sensing range		70 to 300 mm 2.756 to 11.811 in (Note) The sensing range and hysteresis of the diffuse reflective type sensor are specified for white non-glossy paper (200 × 200 mm 7.874 × 7.874 in) as the object.
Sensing object		Opaque, translucent or transparent object(Min. sensing object: Ø0.5 mm Ø0.020 in copper wire) (Note) Make sure to confirm detection with an actual sensor before use.
Hysteresis		15 % or less of operation distance (Note) The sensing range and hysteresis of the diffuse reflective type sensor are specified for white non-glossy paper (200 × 200 mm 7.874 × 7.874 in) as the object.
Repeatability(perpendicular to sensing axis)		0.5 mm 0.020 in or less



Item		Specifications
		Download
Catalog/ Datasheet	CAD	Manual
Current consumption		15 mA or less
Output		PNP open-collector transistor - Maximum source current: 100 mA - Applied voltage: 30 V DC or less (between output and +V) - Residual voltage: 2 V or less (at 100 mA source current), 1 V or less (at 16 mA source current)
Output:Output operation		Switchable either Light-ON or Dark-ON
Output:Short-circuit protection		Incorporated
Response time		1 ms or less
Operation indicator		Orange LED(lights up when the output is ON) (incorporated on the receiver for thru-beam type)
Stability indicator		Green LED(lights up under stable light received condition or stable dark condition) (incorporated on the receiver for thru-beam type)
Power indicator		-




Item		Specifications
		Download
Catalog/ Datasheet	CAD	Manual
		mini-beam type)
Automatic interference prevention function		Incorporated(Two units of sensors can be mounted close together.)
Protection		IP67 (IEC)
Ambient temperature		- 25 to +55°C -13 to +131°C °F (No dew condensation or icing allowed), Storage: -30 to +70°C -22 to +158°C °F
Ambient humidity		35 to 85 % RH, Storage: 35 to 85 % RH
Ambient illuminance		Incandescent light: 3,000 lx or less at the light-receiving face
Voltage withstandability		1,000 V AC for one min. between all supply terminals connected together and enclosure
Insulation resistance		20 MOhm , or more, with 250 V DC megger between all supply terminals connected together and enclosure
Vibration resistance		10 to 500 Hz frequency, 1.5 mm 0.059 in amplitude (10 G max.) in X, Y and Z directions for two hours each



Item		Specifications
		Download
Catalog/ Datasheet	CAD	Manual
		three times each
Emitting element (modulated)		Red LED
Emitting element (modulated):Peak emission wavelength		645 nm 0.025 mil
Material		Enclosure: PBT (polybutylene terephthalate) Lens: acrylic Indicator cover: acrylic
Cable		0.2 mm ² 3-core cabtyre cable, 2 m 6.562 ft long
Cable extension		Extension up to total 100 m 328.084 ft is possible with 0.3 mm ² , or more, cable.
Weight		Net weight: 50 g approx. Gross weight: 60 g approx.
Accessory		-

Accessories (Option)

	Product number	Part number	Product	D
	MS-AJ1	MS-AJ1	-	-



	Product number	Part number	Product	Download
Catalog/ Datasheet		CAD	Manual	
No image	MS-AJ1-M	MS-AJ1-M	-	-
No image	MS-AJ2	MS-AJ2	-	-

View more

Recently checked products

Recently checked product numbers

- CX-423 | Compact Photoelectric Sensor
CX-400 Ver.2 >
- CX-422-P | Compact Photoelectric
Sensor CX-400 Ver.2 >
- CX-422 | Compact Photoelectric Sensor
CX-400 Ver.2 >
- CX-421-P | Compact Photoelectric
Sensor CX-400 Ver.2 >
- CX-421 | Compact Photoelectric Sensor
CX-400 Ver.2 >

Contact Us



Control Components & Electronic Device Products Technical Support

Relays, Couplers, Connectors, Switches, and Other Control Components & Electronic Device Products

Contact Us

FA Sensors & Components

Catalog/Datasheet

CAD

Manual

Download

Support

FA Sensors, PLC ,Eco Power Meters, Times, Counters, Limit Switcheds and Other FA Sensors & Components

Contact Us

Motors

Motors for FA & Industrial Application, Motors for Appliance & Automotive

Contact Us

Guidelines for Ordering and Usage

Requests to customers (FA Sensors & Components [Excluding motors])

Requests to customers (Dedicated to industrial motors)

Components & Devices


Relays / Couplers
Connectors
Switches
Encoders / Potentiometers

FA Sensors & Components

Fiber Sensors	Sensor Options	Static Control Devices
Photoelectric Sensors / Laser Sensors	Wire-Saving Systems	Laser Markers / 2D Code Readers
Micro Photoelectric Sensors	Programmable Controllers / Motion Controller	Machine Vision System

Motors for FA & Industrial Application

AC Servo
Motors for HVAC & Automotive



Cooling Fan

Light Curtains /
Safety
Components

Area Sensors

Inductive
Proximity
Sensors

Particular Use
Sensors

Human
Machine

Energy
Management

Download

Catalog/
Datasheet

CAD

Manual

Measurement
Sensors

