



Contactor relay, 220 V DC, 4 N/O, Screw terminals, DC operation



Part no. **DILA-40(220VDC)**  
**276348**

|  |  |  |
|--|--|--|
| <b>General specifications</b>            |  |  |
| Product name                             |  | Eaton Moeller® series DILA Control relay   |
| Part no.                                 |  | DILA-40(220VDC)  |
| EAN                                      |  | 4015082763480  |
| Product Length/Depth                     |  | 75 millimetre  |
| Product height                           |  | 68 millimetre  |
| Product width                            |  | 45 millimetre  |
| Product weight                           |  | 0.296 kilogram   |
| Compliances                              |  | CE Marked  |
| Certifications                           |  | UL 508<br>CSA Std. C22.2 No. 14-05<br>EN 60947-4-1<br>IEC 60947-4-1<br>VDE<br>IEC/EN 60947-4-1<br>IEC/EN 60947<br>CSA File No.: 012528<br>CSA-C22.2 No. 14-05<br>UL Category Control No.: NKCR<br>VDE 0660<br>UL File No.: E29184<br>CE<br>CSA Class No.: 3211-03<br>CSA<br>EN 60947-5-1<br>UL |
| Product Tradename                        |  | DILA   |
| Product Type                             |  | Control relay  |
| Product Sub Type                         |  | None   |
| Catalog Notes                            |  | Coil terminal markings according to EN 50005<br>Contact numbers according to EN 50011<br>Rated operational current: Switch-on and switch-off conditions based on DC-13, time constant as specified.  |
| <b>Features &amp; Functions</b>          |  |  |
| Features                                 |  | Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module   |
| Fitted with:                             |  | Suppressor circuit<br>Built-in suppressor circuit<br>Positive operation contacts   |
| <b>General information</b>               |  |  |
| Application                              |  | Contactor relays   |
| Degree of protection                     |  | IP20   |
| Shock resistance                         |  | 5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms<br>7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms |
| Lifespan, mechanical                     |  | 20,000,000 Operations (DC operated)  |
| Mounting method                          |  | DIN rail   |
| Operating frequency                      |  | 9000 Operations/h  |
| Overvoltage category                     |  | III  |
| Pollution degree                         |  | 3  |
| Product category                         |  | DILA relays  |
| Protection                               |  | Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)   |
| Rated impulse withstand voltage (Uimp)   |  | 6000 V AC  |
| Voltage type                             |  | DC   |
| <b>Climatic environmental conditions</b> |  |  |
| Ambient operating temperature - min      |  | -25 °C   |
| Ambient operating temperature - max      |  | 60 °C  |

|   |  |   |
|---|--|---|
| Ambient operating temperature (enclosed) - min                    |  | 25 °C   |
| Ambient operating temperature (enclosed) - max                    |  | 40 °C   |
| Ambient storage temperature - min                                 |  | 40 °C   |
| Ambient storage temperature - max                                 |  | 80 °C   |
| Climatic proofing   |  | Damp heat, cyclic, to IEC 60068-2-30<br>Damp heat, constant, to IEC 60068-2-78  |
| <b>Terminal capacities</b>  |  |   |
| Terminal capacity (flexible with ferrule)                         |  | 1 x (0.75 - 2.5) mm <sup>2</sup> , Screw terminals<br>2 x (0.75 - 2.5) mm <sup>2</sup> , Screw terminals  |
| Terminal capacity (solid)   |  | 2 x (0.75 - 2.5) mm <sup>2</sup> , Screw terminals<br>1 x (0.75 - 4) mm <sup>2</sup> , Screw terminals  |
| Terminal capacity (solid/stranded AWG)                            |  | 18 - 14, Screw terminals  |
| Stripping length (main cable)                                     |  | 10 mm   |
| Screw size  |  | M3.5, Terminal screw  |
| Screwdriver size  |  | 2, Terminal screw, Pozidriv screwdriver<br>0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver   |
| Tightening torque   |  | 1.2 Nm, Screw terminals   |
| <b>Electrical rating</b>  |  |   |
| Conventional thermal current $I_{th}$ at 60°C (3-pole, open)      |  | 16 A  |
| Rated operational current ( $I_e$ )                               |  | 1 A at 220 V, DC L/R ≤ 15 ms (with 1 contact in series)<br>5 A at 220 V, DC L/R ≤ 15 ms (with 3 contacts in series)<br>6 A at 110 V, DC L/R ≤ 15 ms (with 3 contacts in series)<br>2 A at 110 V, DC L/R ≤ 50 ms (with 3 contacts in series)<br>3 A at 110 V, DC L/R ≤ 15 ms (with 1 contact in series)<br>4 A at 24 V, DC L/R ≤ 50 ms (with 3 contacts in series)<br>4 A at 60 V, DC L/R ≤ 50 ms (with 3 contacts in series)<br>6 A at 60 V, DC L/R ≤ 15 ms (with 1 contact in series)<br>10 A at 60 V, DC L/R ≤ 15 ms (with 2 contacts in series)<br>10 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series)<br>1 A at 220 V, DC L/R ≤ 50 ms (with 3 contacts in series)<br>16 A |
| Rated operational current ( $I_e$ ) at AC-15, 220 V, 230 V, 240 V |  | 4 A   |
| Rated operational current ( $I_e$ ) at AC-15, 380 V, 400 V, 415 V |  | 4 A   |
| Rated operational current ( $I_e$ ) at AC-15, 500 V               |  | 1.5 A   |
| Rated insulation voltage ( $U_i$ )                                |  | 690 V   |
| Rated operational voltage ( $U_e$ ) at AC - max                   |  | 690 V   |
| Short-circuit protection rating without welding                   |  | 10 A gG/gL, 500 V, Max. Fuse, Contacts  |
| Safe isolation  |  | 400 V AC, Between coil and auxiliary contacts, According to EN 61140<br>400 V AC, Between auxiliary contacts, According to EN 61140   |
| Switching capacity (auxiliary contacts, general use)              |  | 15 A, 600 V AC, (UL/CSA)<br>1 A, 250 V DC, (UL/CSA)   |
| Switching capacity (auxiliary contacts, pilot duty)               |  | P300, DC operated (UL/CSA)<br>A600, AC operated (UL/CSA)  |
| <b>Magnet system</b>  |  |   |
| Duty factor   |  | 100 %   |
| Pick-up voltage   |  | 0.7 - 1.3 V DC x $U_c$ (at 24 V: without auxiliary contact module and at ambient air temperature + 40 °C)<br>0.8 - 1.1 V DC x $U_c$   |
| Power consumption (pick-up) at DC                                 |  | 2.6 W   |
| Power consumption (sealing) at DC                                 |  | 2.6 W   |
| Rated control supply voltage ( $U_s$ ) at AC, 50 Hz - min         |  | 0 V   |
| Rated control supply voltage ( $U_s$ ) at AC, 50 Hz - max         |  | 0 V   |
| Rated control supply voltage ( $U_s$ ) at AC, 60 Hz - min         |  | 0 V   |
| Rated control supply voltage ( $U_s$ ) at AC, 60 Hz - max         |  | 0 V   |
| Rated control supply voltage ( $U_s$ ) at DC - min                |  | 220 V   |
| Rated control supply voltage ( $U_s$ ) at DC - max                |  | 220 V   |
| Switching time (DC operated, make contacts, closing delay) - max  |  | 31 ms   |
| Switching time (DC operated, make contacts, opening delay) - max  |  | 12 ms   |
| Voltage tolerance   |  | Smoothed DC, three-phase bridge rectifiers or smoothed double-wave rectification  |
| <b>Communication</b>  |  |   |
| Connection  |  | Screw terminals   |
| Connection to SmartWire-DT  |  | No  |
| <b>Contacts</b>   |  |   |

|  |  |  |
|--|--|--|
| Code number  |  | 40D  |
| Control circuit reliability  |  | $\lambda < 5 \times 10^{-7}$ (1 failure at 2,000,000 operations for $U\# = 24$ V DC, $U_{min} = 17$ V, $I_{min} = 5.4$ mA)       |
| Number of auxiliary contacts (change-over contacts)                              |  | 0  |
| Number of contacts (normally closed contacts)                                    |  | 0  |
| Number of contacts (normally open contacts)                                      |  | 4  |
| Number of auxiliary contacts (normally closed contacts)                          |  | 0  |
| Number of auxiliary contacts (normally open contacts)                            |  | 4  |
| <b>Design verification</b>   |  |  |
| Equipment heat dissipation, current-dependent P <sub>vid</sub>                   |  | 0 W  |
| Heat dissipation capacity P <sub>diss</sub>                                      |  | 0 W  |
| Heat dissipation per pole, current-dependent P <sub>vid</sub>                    |  | 1 W  |
| Rated operational current for specified heat dissipation (I <sub>n</sub> )       |  | 15.5 A   |
| Static heat dissipation, non-current-dependent P <sub>vs</sub>                   |  | 3 W  |
| 10.2.2 Corrosion resistance  |  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures                         |  | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       |  | Meets the product standard's requirements.   |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects |  | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 |  | Meets the product standard's requirements.   |
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of assemblies  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   |  | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components                           |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections                                |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |  | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength   |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material                         |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 9.0

|   |   |           |
|---|---|-----------|
| Low-voltage industrial components (EG000017) / Contactor relay (EC000196)   |   |           |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Contactor relay (ecl@ss13-27-37-10-01 [AAB716019]) |   |           |
| Rated control supply voltage AC 50 Hz   | V | 0 - 0     |
| Rated control supply voltage AC 60 Hz   | V | 0 - 0     |
| Rated control supply voltage DC   | V | 220 - 220 |
| Voltage type for actuating  |   | DC        |
| Rated operation current   | A | 16        |
| Rated operation current I <sub>e</sub> , 400 V  | A | 4         |
| Mounting method   |   | DIN rail  |
| With LED indication   |   | No        |
| Suitable for manual operation   |   | No        |
| Interface   |   | No        |
| Number of auxiliary contacts as normally closed contact   |   | 0         |
| Number of auxiliary contacts as normally open contact   |   | 4         |
| Number of auxiliary contacts as normally closed contact, delayed switching  |   | 0         |
| Number of auxiliary contacts as normally open contact, leading  |   | 0         |

|   |    |                  |
|---|----|------------------|
| Number of auxiliary contacts as change-over contact |    | 0                |
| Operating voltage AC 50 Hz                          | V  | 17 - 500         |
| Operating voltage AC 60 Hz                          | V  | 17 - 500         |
| Operating voltage DC                                | V  | 24 - 220         |
| Voltage type (operating voltage)                    |    | AC/DC            |
| Rated switch current                                | A  | 16               |
| Connection type auxiliary circuit                   |    | Screw connection |
| Width   | mm | 45               |
| Height  | mm | 68               |
| Depth   | mm | 75               |