



# Mini circuit breaker, E-Frame, 20A, 2 pole, 480Y/277VAC, 25kA max, bolt on

EDB24020

Product availability: Stock - Normally stocked in distribution facility

Price\*: 536.00 USD

#### Main

| Range of Product          | 125 A Frame EDB-EGB-EJB   |
|---------------------------|---------------------------|
| Product or Component Type | Miniature circuit-breaker |
| Device short name         | EDB                       |
| Module type               | E-Frame                   |
| Trip unit rating          | 875 A                     |

### Complementary

| Line Rated Current          | 20 A  |
|-----------------------------|---|
| maximum operating voltage   | 480Y/277 V AC   |
| AWG gauge                   | AWG 12AWG 6 aluminium<br>AWG 14AWG 6 copper   |
| Breaking capacity           | 18 kA 277 V AC<br>25 kA 240 V AC<br>18 kA 480Y/277 V AC<br>25 kA 120 V AC<br>25 kA 120/240 V AC |
| Circuit breaker application | HID rated<br>HACR rated   |
| Electrical connection       | Lugs aluminium  |
| Holding Current             | 270 A   |
| local signalling            | Trip indicator  |
| Mounting Mode               | Bolt-on   |
| Number of poles             | 2   |
| Number of spaces            | 2   |
| Number of spaces required   | 2   |
| Product destination         | NF panelboard   |
| Protection Type             | Short-circuit<br>Overload   |
| Trip unit technology        | Thermal-magnetic  |
| Breaking capacity code      | D   |
| Tightening torque           | 30.09 lbf.in (3.4 N.m) 0.0040.02 in² (2.516 mm²) (AWG 14AWG 6)                                  |
| Height                      | 5.66 in (143.76 mm)   |
| Width                       | 1.96 in (49.78 mm)  |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Depth      | 4.05 in (102.87 mm) |
|------------|---------------------|
| Net Weight | 3 lb(US) (1.4 kg)   |

### **Environment**

| Product Certifications                   | cULus          |
|--|----------------|
| Ambient Air Temperature for<br>Operation | 104 °F (40 °C) |

## Ordering and shipping details

| Category          | US10DE200931 |
|-------------------|--------------|
| Discount Schedule | 0DE2         |
| GTIN              | 785901879015 |
| Returnability     | Yes          |
| Country of origin | MX           |

## **Packing Units**

| Unit Type of Package 1       | PCE                   |
|------------------------------|-----------------------|
| Number of Units in Package 1 | 1                     |
| Package 1 Height             | 3.800 in (9.652 cm)   |
| Package 1 Width              | 6.200 in (15.748 cm)  |
| Package 1 Length             | 9.900 in (25.146 cm)  |
| Package 1 Weight             | 2.45 lb(US) (1.11 kg) |

## **Contractual warranty**

Warranty 18 months

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

## Well-being performance

| Well-being performance  |  |
|-------------------------|--|
| Mercury Free            |  |
| Rohs Exemption Informat | ion Yes  |
| Reach Regulation        | REACh Declaration  |
| Eu Rohs Directive       | Pro-active compliance (Product out of EU RoHS legal scope)   |
| China Rohs Regulation   | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information. |