



Mini circuit breaker, E-Frame, 125A, 3 pole, 480Y/277VAC, 25kA max, bolt on

EDB34125

Product availability: Stock - Normally stocked in distribution facility

Price*: 2,421.00 USD

Main

Range of Product	125 A Frame EDB-EGB-EJB
Product or Component Type	Miniature circuit-breaker
Device short name	EDB
Module type	E-Frame
Trip unit rating	2300 A

Complementary

Line Rated Current	125 A
maximum operating voltage	480Y/277 V AC
AWG gauge	AWG 12AWG 2/0 aluminium
	AWG 14AWG 2/0 copper
Breaking capacity	18 kA 277 V AC
	25 kA 240 V AC
	18 kA 480Y/277 V AC
	25 kA 120 V AC
	25 kA 120/240 V AC
Circuit breaker application	HACR rated
Electrical connection	Lugs aluminium
Holding Current	1000 A
local signalling	Trip indicator
Mounting Mode	Bolt-on
Number of poles	3
Number of spaces	3
Number of spaces required	3
Product destination	NF panelboard
Protection Type	Overload
	Short-circuit
Trip unit technology	Thermal-magnetic
Breaking capacity code	D
Tightening torque	34.5 lbf.in (3.9 N.m) 0.0040.009 in² (2.56 mm²) (AWG 14AWG 10) 49.6 lbf.in (5.6 N.m) 0.020.1 in² (1070 mm²) (AWG 8AWG 2/0)
Height	5.66 in (143.76 mm)
Width	2.94 in (74.68 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Depth	4.05 in (102.87 mm)
Net Weight	4 lb(US) (1.8 kg)

Environment

Product Certifications	cULus
Ambient Air Temperature for Operation	104 °F (40 °C)

Ordering and shipping details

Category	US10DE200931	
Discount Schedule	0DE2	
GTIN	785901072966	
Returnability	Yes	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE
	. 02
Number of Units in Package 1	1
Package 1 Height	4.800 in (12.192 cm)
Package 1 Width	6.200 in (15.748 cm)
Package 1 Length	9.900 in (25.146 cm)
Package 1 Weight	3.651 lb(US) (1.656 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	392
Package 2 Height	40.000000000 in (101.6 cm)
Package 2 Width	40.000000000 in (101.6 cm)
Package 2 Length	48.0000000000 in (121.92 cm)
Package 2 Weight	1470.00 lb(US) (666.78 kg)

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Well-being performance		
②	Mercury Free	
Ø	Rohs Exemption Information	Yes
Rea	ch Regulation	REACh Declaration
Eu f	Rohs Directive	Compliant with Exemptions
Chir	na Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.