



MATERIAL FACT SHEET

166085 FX3U-64DP-M

General Data

| | |
|---------------------|--------------------------|
| Product Hierarchy | IAD213 |
| | Compact PLC |
| | FX3U |
| Ext. Material Group | 10 STANDARD ITEM |
| ABC Indicator | A (Available from Stock) |

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_1A/EUR/en/p/000000000000166085

FA-COM PLC: Network Module

| | |
|-------------------|-----------------|
| Series | MELSEC-F SERIES |
| Type | MASTER STATION |
| Network Interface | PROFIBUS-DP |

Product Dimensions & Weight

| | |
|-------------|-----|
| Width (mm) | 43 |
| Height (mm) | 90 |
| Depth (mm) | 87 |
| Weight (kg) | 0,2 |

Logistic Dimensions & Gross Weight

| | |
|-------------------|-------|
| Length (cm) | 10,0 |
| Width (cm) | 10,0 |
| Height (cm) | 9,0 |
| Gross Weight (kg) | 0,207 |
| Volume (cdm) | 0,900 |

Stock Data

| | |
|------------------------------|-----|
| Planned Delivery Time (Days) | 128 |
|------------------------------|-----|

Life Cycle

| | |
|-------------|----------------------|
| Sales Start | 15.11.2005 |
| Predecessor | 141644 / FX2N-64DP-M |

Additional Product Information

| | |
|----------------------------|------------------|
| Binding Tariff Information | DEBTI-10857/21-1 |
| BTI validity date | 13.06.2024 |
| Battery included | NO |

Export Data

| | |
|--|------------|
| Commodity Code | 85176200 |
| Legal Control (Dual Use List) | Not Listed |
| Country of Origin | Japan (JP) |
| Preference Status (Supplier Declaration) | Non EU |

Environmental

| | |
|----------------------------|-----------|
| REACH Limit Exceeded | NO |
| Dangerous Goods Class | NO |
| Dangerous Goods Identifier | NO |
| RoHS Compliance | COMPLIANT |
| WEEE | B2B |

Conformity

| | |
|--------|---------------|
| CE | COMPLIANT |
| UL/cUL | COMPLIANT |
| EAC | NON-COMPLIANT |

| | |
|--------------------|-----------|
| Shipping Approvals | DNV GL,LR |
| UKCA | COMPLIANT |

Documentation & Media Data

| | |
|----------------------------|---|
| Manual URL Indicator | https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=FX3U-64DP-M&doc-lang=en |
| Certificates URL Indicator | https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=FX3U-64DP-M&doc-lang=en |
| CAD URL Indicator | https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=FX3U-64DP-M&doc-lang=en |

Product Packaging

| | |
|-------------------|----|
| Cardboard (g) | 38 |
| Other paper (g) | 0 |
| Aluminum (g) | 0 |
| Steel (g) | 0 |
| Styrofoam (g) | 0 |
| Other plastic (g) | 0 |
| Wood (g) | 0 |
| Glass (g) | 0 |
| Others (g) | 0 |

Compatible products

| Material | Description / Price List Text / Classification |
|------------------------|--|
| 140008 | PROFICON-PLUS PLC Profibus connector with termination resistor Class 100100304: FA-HMI: Other Option |