



Linergy FT - Comb busbar - 63 A -3 tap-offs - 54 mm pitch

GV2G354

Main

Range	Linergy
Product Name	FT
Device Short Name	GV2G
Product Or Component Type	Comb busbar
Accessory / Separate Part Category	Connection accessory
Poles Description	3P
Range Compatibility	TeSys Deca TeSys GV2 TeSys K TeSys U
Number Of Tap-Offs	3
[Ith] Conventional Free Air Thermal Current	63 A
Connection Pitch	54 mm

Complementary

Mounting Location	On terminal
[Ui] Rated Insulation Voltage	690 V
Length	152 mm
Net Weight	0.06 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1 cm
Package 1 Width	3.1 cm
Package 1 Length	15.1 cm
Package 1 Weight	64 g
Unit Type Of Package 2	S01
Number Of Units In Package 2	70
Package 2 Height	15 cm
Package 2 Width	15 cm
Package 2 Length	40 cm
Package 2 Weight	4.589 kg

Unit Type Of Package 3	P06
Number Of Units In Package 3	2240
Package 3 Height	77 cm
Package 3 Width	80 cm
Package 3 Length	60 cm
Package 3 Weight	159.06 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
9	Mercury Free	
⊘	Rohs Exemption Information	Yes


Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

GV2G354

Dimensions Drawings

Sets of Busbars GV2G345 and GV2G354



	1
GV2G345 (3 x 45 mm)	134
GV2G354 (3 x 54 mm)	152