

Product datasheet

Specifications



TeSys, Voltage release, TeSys GV4, MX coil coil, 24VAC/DC

GV4AS027

Main

| | |
|------------------------------|------------------------------------|
| Range | TeSys |
| Device Short Name | MX |
| Product Or Component Type | Voltage release |
| Device Application | Control |
| Range Compatibility | TeSys TeSys GV4 TeSys TeSys BV4 |
| Voltage Release Type | Shunt trip release |
| [Uc] Control Circuit Voltage | 24 V AC 50/60 Hz 24 V DC |

Complementary

| | |
|---|--|
| [Ui] Rated Insulation Voltage | 24 V conforming to IEC 60947-1 |
| Threshold Tripping Voltage | 0.7...1.1 Un failsafe opening < 0.7 Un possible opening |
| Impulse Duration | >= 20 ms |
| Mounting Mode | Internal mounting |
| Maximum Inrush Power In Va | 6 VA |
| Maximum Inrush Power In W | 4 W |
| Maximum Hold-In Power Consumption In Va | 10 VA |
| Maximum Hold-In Power Consumption In W | 1 W |
| Mechanical Durability | 20000 cycles |
| Operating Time | < 50 ms |
| Connections - Terminals | Spring terminals 1 0.5...1.5 mm² - cable stiffness: flexible without cable end |
| Wire Stripping Length | 8 mm |

Environment

| | |
|------------------|----------|
| Quantity Per Set | Set of 1 |
|------------------|----------|

Packing Units

| | |
|------------------------------|----------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 3.500 cm |
| Package 1 Width | 6.000 cm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|------------------------------|-----------|
| Package 1 Length | 8.500 cm |
| Package 1 Weight | 64.000 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 10 |
| Package 2 Height | 9.000 cm |
| Package 2 Width | 13.000 cm |
| Package 2 Length | 18.500 cm |
| Package 2 Weight | 690.000 g |
| Unit Type Of Package 3 | S03 |
| Number Of Units In Package 3 | 120 |
| Package 3 Height | 30.000 cm |
| Package 3 Width | 30.000 cm |
| Package 3 Length | 40.000 cm |
| Package 3 Weight | 8.500 kg |

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency

Well-being performance

| | | |
|--------------------------|---|---|
| ✓ | Mercury Free | |
| ✓ | Rohs Exemption Information | Yes |
| Eu Rohs Directive | Compliant with Exemptions | |
| China Rohs Regulation | China RoHS declaration | Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile | |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins | |
| Circularity Profile | End of Life Information | |