

Product data sheet

Specifications



Voltage release, TeSys GV7, MX shunt trip, 200 to 240VAC50/60Hz

GV7AS207

 **Discontinued on:** May 17, 2022

Product availability: Non-Stock - Not normally stocked in distribution facility

 **Discontinued**

Main

| | |
|---------------------------|---|
| Range | TeSys |
| Product Or Component Type | Shunt trip |
| Device Short Name | GV7AS |
| Device Application | Control |
| Range Compatibility | TeSys TeSys GV5 TeSys TeSys GV6 TeSys TeSys GV7 |

Complementary

| | |
|---------------------------------|---|
| [Uc] Control Circuit Voltage | 200...240 V AC 50/60 Hz |
| Control Circuit Voltage Limits | 0.7...1.1 Un |
| [Ui] Rated Insulation Voltage | 690 V AC IEC 60947-1 600 V AC UL 508 600 V AC CSA C22.2 No 14 |
| Threshold Tripping Voltage | 0.2...0.75 Ue |
| Inrush Power In Va | 10 VA AC |
| Hold-In Power Consumption In Va | 5 VA AC |
| Operating Time | < 50 ms IEC 60947-1 |
| On-Load Factor | 100 % |
| Connections - Terminals | screw clamp terminals 1 0.00 in ² (1 mm ²)flexible with cable end screw clamp terminals 1 0.00 in ² (1.5 mm ²)flexible without cable end screw clamp terminals 1 0.00 in ² (1.5 mm ²)solid |
| Tightening Torque | 1.2 N.m screw clamp terminals |
| Net Weight | 0.23 lb(US) (0.105 kg) |
| Quantity Per Set | Set of 10 |

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US10I1122366 |
| Discount Schedule | 0I11 |
| Gtin | 3389110566956 |
| Returnability | No |
| Country Of Origin | FR |

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|------------------------------|------------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 1.69 in (4.3 cm) |
| Package 1 Width | 3.94 in (10 cm) |
| Package 1 Length | 5.91 in (15 cm) |
| Package 1 Weight | 5.33 oz (151 g) |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability





Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

| | | |
|---|---|-----|
|  | Reach Free Of Svhc | |
|  | Toxic Heavy Metal Free | |
|  | Mercury Free | |
|  | Rohs Exemption Information | Yes |
| | | |
| Reach Regulation | REACH Declaration | |
| Eu Rohs Directive | Compliant EU RoHS Declaration | |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) | |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. | |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov | |