# **Product data sheet**

Specifications





## MAN-STARTER SHORT CIR CONTACT 575VAC 1

GVAM11

Product availability: Stock - Normally stocked in distribution facility

Price\*: 35.70 USD

#### Main

Range TeSys	
· ······•	TeSys Deca
Device Short Name	GVAM
Product Or Component Type	Auxiliary contact block
Product Compatibility	GV2L GV2ME GV2RT GV3L GV2P GV3P GV3L
Range Compatibility	TeSys TeSys GV3 GV3P circuit breaker TeSys GV3 GV3L circuit breaker
Mounting Location	Left side
Auxiliary Contacts Operation	Short-circuit signal 1 C/O
Pole Contact Composition	1 C/O
Complementary	
[Ui] Rated Insulation Voltage	690 V IEC 60947-1 300 V UL 508 300 V CSA C22.2 No 14
[Ue] Rated Operational Voltage	24240 V AC 2460 V DC
[Ith] Conventional Free Air Thermal Current	2.5 A for fault signalling
Mechanical Durability	100000 cycles
Minimum Switching Current	5 mA
Minimum Switching Voltage	17 V
Protection Type	GB2CB circuit breaker GG fuse 10 A
Rated Operational Power In Va	36 VA 24 V AC-14 1000 cycles 1.5 A 48 VA 48 V AC-14 1000 cycles 1 A 72 VA 110127 V AC-14 1000 cycles 0.5 A 72 VA 230240 V AC-14 1000 cycles 0.3 A
Rated Operational Power In W	120 W 240 V DC-13 100000 cycles 140 W 110 V DC-13 100000 cycles 140 W 24 V DC-13 100000 cycles 180 W 60 V DC-13 100000 cycles 240 W 48 V DC-13 100000 cycles 15 W 48 V DC-13 10000 cycles

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

24 W 24 V DC-13 1000 cycles 9 W 60 V DC-13 1000 cycles

Tightening Torque	12.39 lbf.in (1.4 N.m) screw clamp terminals
Height	3.50 in (89 mm)
Width	0.37 in (9.3 mm)
Depth	2.60 in (66 mm)
Net Weight	0.12 lb(US) (0.055 kg)
Color	Dark grey

### **Environment**

Environmental Characteristic	Normal environment	
Product Certifications	UKCA	

### Ordering and shipping details

Category	US10I1122367	
Discount Schedule	0111	
Gtin	3389110343564	
Returnability	Yes	
Country Of Origin	CZ	

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.59 in (1.5 cm)
Package 1 Width	2.76 in (7.0 cm)
Package 1 Length	3.54 in (9.0 cm)
Package 1 Weight	1.38 oz (39 g)
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	3.94 in (10.0 cm)
Package 2 Width	4.13 in (10.5 cm)
Package 2 Length	6.02 in (15.3 cm)
Package 2 Weight	15.52 oz (440 g)
Unit Type Of Package 3	S02
Number Of Units In Package 3	60
Package 3 Height	5.91 in (15 cm)
Package 3 Width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)
Package 3 Weight	6.49 lb(US) (2.944 kg)

### **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>②</b>	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
<b>②</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Connections and Schema

## **Short-Circuit Signalling Contacts**

GVAM11