

# Product datasheet

Specifications



## EasyPact TVS - auxiliary contact mounted on left hand side - NO+NC

GZ1AN11

### Main

Range Of Product	Easy TeSys Power
Range	Easy TeSys
Product Or Component Type	Auxiliary contact block
Device Short Name	GZ1AN
Connections - Terminals	Screw clamp terminals 1 cable(s) 1...2.5 mm <sup>2</sup> solid Screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> solid Screw clamp terminals 1 cable(s) 0.75...2.5 mm <sup>2</sup> flexible without cable end Screw clamp terminals 2 cable(s) 0.75...2.5 mm <sup>2</sup> flexible without cable end Screw clamp terminals 2 cable(s) 0.75...1.5 mm <sup>2</sup> flexible with cable end Screw clamp terminals 1 cable(s) 0.75...1.5 mm <sup>2</sup> flexible with cable end

### Complementary

Range Compatibility	EasyPact EasyPact TVS GZ1E circuit breaker
Mounting Location	Left side
Auxiliary Contacts Operation	Instantaneous 1 NO + 1 NC
Pole Contact Composition	1 NO + 1 NC
[Ui] Rated Insulation Voltage	690 V conforming to IEC 60947-1
[Ue] Rated Operational Voltage	48...690 V AC 24...240 V DC
[Ith] Conventional Free Air Thermal Current	6 A
Protection Type	GG fuse 10 A
Mechanical Durability	100000 cycles
Minimum Switching Current	5 mA
Minimum Switching Voltage	17 V
Rated Operational Power In Va	300 VA at 48 V AC-15 - electrical durability: 70000 cycles 400 VA at 690 V AC-15 - electrical durability: 70000 cycles 500 VA at 110...127 V AC-15 - electrical durability: 70000 cycles 500 VA at 500 V AC-15 - electrical durability: 70000 cycles 650 VA at 440 V AC-15 - electrical durability: 70000 cycles 720 VA at 230...240 V AC-15 - electrical durability: 70000 cycles 850 VA at 380...415 V AC-15 - electrical durability: 70000 cycles
Rated Operational Power In W	120 W at 240 V DC-13 - electrical durability: 70000 cycles 140 W at 110 V DC-13 - electrical durability: 70000 cycles 140 W at 24 V DC-13 - electrical durability: 70000 cycles 180 W at 60 V DC-13 - electrical durability: 70000 cycles 240 W at 48 V DC-13 - electrical durability: 70000 cycles
Height	89 mm
Width	9.3 mm
Depth	66 mm

---

Net Weight	0.05 kg
------------	---------

## Packing Units

---

Unit Type Of Package 1	PCE
------------------------	-----

---

Number Of Units In Package 1	1
------------------------------	---

---

Package 1 Height	1.500 cm
------------------	----------

---

Package 1 Width	6.500 cm
-----------------	----------

---

Package 1 Length	8.500 cm
------------------	----------

---

Package 1 Weight	43.300 g
------------------	----------

---

Unit Type Of Package 2	BB1
------------------------	-----

---

Number Of Units In Package 2	10
------------------------------	----

---

Package 2 Height	9.500 cm
------------------	----------

---

Package 2 Width	9.500 cm
-----------------	----------

---

Package 2 Length	15.000 cm
------------------	-----------

---

Package 2 Weight	488.000 g
------------------	-----------

---

Unit Type Of Package 3	S02
------------------------	-----

---

Number Of Units In Package 3	60
------------------------------	----

---

Package 3 Height	15.000 cm
------------------	-----------

---

Package 3 Width	30.000 cm
-----------------	-----------

---

Package 3 Length	40.000 cm
------------------	-----------

---

Package 3 Weight	3.156 kg
------------------	----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Compliant

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Weee**

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Circularity Profile**

[End of Life Information](#)