

Specifications



Product specifications	
TYPE	Motor circuit protector
AMPERAGE RATING	30 A
VOLTAGE RATING	480 V
TRIP TYPE	T98
FRAME SIZE	Frame J-K
MAGNETIC TRIP RANGE	90-300 A
VOLTAGE - MAX	600 Y/347 V
SERIES	Series G
TERMINAL MATERIAL	Non-aluminum
NUMBER OF POLES	Three-pole

Resources	
APPLICATION NOTES	Application of Tap Rules to Molded Case Breaker Terminals
	Application of Multi-Wire Terminals for Molded Case Circuit Breakers
BROCHURES	Current limiting molded case circuit breaker module product aid
	StrandAble terminals product aid
	Comprehensive circuit protection for control panel applications
	Motor protection circuit breakers product aid
	High performance operating handles for Series G circuit breakers product aid
	Multi-wire lugs product aid
	Series G MCCB quick selector
	Plug-in adapters for molded case circuit breakers product aid
	Molded case circuit breakers providing higher levels of selective coordination product aid
	Power metering and monitoring with Modbus RTU product aid
	Circuit breaker motor operators product aid
	Current limiting molded case circuit breaker module for series G, JG and CL
CATALOGS	Breaker service centers
	Circuit Protection, Molded Case Circuit Breakers, Volume 4, Tab 2
MULTIMEDIA	Flex shaft handle installation tutorial
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - HMCPE030H1C
	NG and ND-Frame molded case circuit breakers
	MOEM MCCB product selection guide
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights
Reserved.

Eaton is a registered trademark.

All other trademarks are property of
their respective owners.

Follow us on social media to get the latest
product and support information.

