

SIEMENS LOW VOLTAGE MOLDED CASE CIRCUIT BREAKER WITH THERMAL -  
MAGNETIC TRIP. QR FRAME STANDARD 40C BREAKER. 250A 3-POLE (65KA AT 240V).  
SPECIAL FEATURES: LINE/LOAD SIDE LUGS (TA1QR300) WIRE RANGE 6AWS - 1/0 AWS  
(AL/CU).

Image similar

Article Number (Market Facing Number)	HQR23B250L   US2:HQR23B250L
Product Description	SIEMENS LOW VOLTAGE MOLDED CASE CIRCUIT BREAKER WITH THERMAL - MAGNETIC TRIP. QR FRAME STANDARD 40C BREAKER, 250A 3-POLE (65KA AT 240V). SPECIAL FEATURES: LINE/LOAD SIDE LUGS (TA1QR300) WIRE RANGE 6AWS - 1/0 AWS (AL/CU).
Product family	Not available
Product Lifecycle (PLM)	PM300:Active Product

Price Group	ND5
List Price	Show prices
Customer Price	Show prices
Metal Factor	None

Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	14 Day/Days
Net Weight (lb)	4.519 lb
Packaging Dimension	4.331 x 7.087 x 3.937
Package size unit of measure	Inch
Quantity Unit	1 Piece
Packaging Quantity	1

EAN	Not available
UPC	804766137037
Commodity Code	8536200020
LKZ_FDB/ CatalogID	LV10.1
Product Group	5200
Group Code	P320
Country of origin	Mexico
Compliance with the substance restrictions according to RoHS directive	not available
Returnable	Yes
WEEE (2012/19/EU) Take-Back Obligation	No
REACH Art. 33 Duty to inform according to the current list of candidates	
SCIP number	Not available

	Version	Classification
eClass	12	27-37-13-92
eClass	14	27-37-13-92
eClass	6	27-37-92-01
eClass	7.1	27-37-92-01
eClass	8	27-37-92-01
eClass	9	27-37-92-01
eClass	9.1	27-37-92-01
ETIM	7	EC002498
ETIM	8	EC002498
ETIM	9	EC002498
UNSPSC	15	39-12-15-21

