

ITY-E-TW010B-U
ITYS-E 1kVA 230V ONLU S+
Strong points

- Best electrical protection
- Robust and versatile

General characteristics

- True online double conversion technology (VFI)
- Constant output voltage and frequency regulation
- Automatic bypass supplies the loads in the event of overloads or faults
- Compact tower UPS system
- Easy connections via sockets or terminals
- Wide input voltage tolerance
- Manual bypass for periodic or emergency maintenance

Compliance with standards

- EN 62040-1
- EN 62040-2
- CE

Access to resources (ex: manuals)

Compact tower UPS system saves space in the operating environment.

Classification

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149

Commerce

Description (240 char.)	ITYS-E 1000VA/800W 230V 50Hz ON-LINE DOUBLE CONVERSION (VFI), RS232 WITH UNIVERSAL SOCKET, NOT CE
Effective date	2014-06-01
Country of origin	CN
Length of the product unit	0.22
Width of the product unit	0.145
Depth of the product unit	0.285
Weight	16

Logistics

GTIN/EAN	8027122576819
Customs number	8504409590
Weight of the packing unit	16
Length of the packing unit	0.285
Width of the packing unit	0.145
Depth of the packing unit	0.22

Technical Characteristics

Depth	285
Height	220
In/out	1/1
Output voltage	230
Rated frequency	50/50
Width	145
Sn	1
Pn	0.8
Conf	C1
Input voltage	230
Rate (min)	1
Rate (max)	1
Life Time	03-05
Typical Backup Time	8
Configuration	UPS Single Unit(s) with Bypass