

ITY-E-TW030B
ITYS-E 3kVA 230V ONL
Strong points

- Best electrical protection
- Robust and versatile

General characteristics

- True online double conversion technology (VFI)
- Constant output voltage and frequency regulation
- Automatic bypass supplies the loads in the event of overloads or faults
- Compact tower UPS system
- Easy connections via sockets or terminals
- Wide input voltage tolerance
- Manual bypass for periodic or emergency maintenance

Compliance with standards

- EN 62040-1
- EN 62040-2
- CE

Access to resources (ex: manuals)

Compact tower UPS system saves space in the operating environment.

Classification

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149

Commerce

Description (240 char.)	ITYS-E 3000VA/2400W 230V 50Hz ON-LINE DOUBLE CONVERSION (VFI), RS232
Effective date	2015-01-01
Country of origin	CN
Length of the product unit	0.32
Width of the product unit	0.19
Depth of the product unit	0.425
Weight	37

ETIM - Electrical characteristics

Input voltage [V]	160..300
Primary frequency [Hz]	45..65
Number of phases primary	1
Output voltage [V]	208..240
Secondary frequency [Hz]	47..53
Output effective power [W]	2400
Output apparent power [VA]	3000
Number of phases secondary	1
SNMP	Yes
Voltage type	AC
Max. voltage distortion output (linear load) [%]	3
Output power factor	0.8

ETIM - Mechanical characteristics

Height [mm]	320
Width [mm]	190
Depth [mm]	425
Weight [kg]	37
Construction type	Free standing model
Input connection	C20
Number of output connections C13	4
Number of output connections fixed connection	1

ETIM - Technical features

USB interface	Yes
Suitable for network-management	Yes
USV- technology	Online
Overall efficiency [%]	91
Potential free switch contact	No
Auto shut down function	Yes

Logistics

GTIN/EAN	8027122563994
Customs number	8504409590

Weight of the packing unit	37
Length of the packing unit	0.425
Width of the packing unit	0.19
Depth of the packing unit	0.32
Technical Characteristics	
Depth	425
Height	320
In/out	1/1
Output voltage	230
Rated frequency	50/50
Width	190
Sn	3
Pn	2.4
Conf	C1
Input voltage	230
Rate (min)	3
Rate (max)	3
Life Time	03-05
Typical Backup Time	8
Configuration	UPS Single Unit(s) with Bypass