

ITY-E-TW060LB
ITYS-E 6kVA 230V ONLU-B CH+
Strong points

- Best electrical protection
- Robust and versatile

General characteristics

- True online double conversion technology (VFI)
- Constant output voltage and frequency regulation
- Automatic bypass supplies the loads in the event of overloads or faults
- Compact tower UPS system
- Easy connections via sockets or terminals
- Wide input voltage tolerance
- Manual bypass for periodic or emergency maintenance

Compliance with standards

- EN 62040-1
- EN 62040-2
- CE

Access to resources (ex: manuals)

Compact tower UPS system saves space in the operating environment.

Classification

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149

Commerce

Description (240 char.)	ITYS-E 6000VA/4800W 230V 50Hz WITH POWERFUL BATTERY CHARGER FOR LONGAUTONOMY FOR LONGANTONOMY EXTERNAL BATTERY ON-LINE DOUBLE CONVERSION (VFI),RS232
Effective date	2014-06-01
Country of origin	CN
Length of the product unit	0.32
Width of the product unit	0.19
Depth of the product unit	0.37
Weight	37.5

ETIM - Electrical characteristics

Input voltage [V]	160..300
Primary frequency [Hz]	45..65
Number of phases primary	1
Output voltage [V]	208..240
Secondary frequency [Hz]	47..53
Output effective power [W]	4800
Output apparent power [VA]	6000
Number of phases secondary	1
SNMP	Yes
Voltage type	AC
Max. voltage distortion output (linear load) [%]	3
Output power factor	0.8

ETIM - Mechanical characteristics

Height [mm]	320
Width [mm]	190
Depth [mm]	370
Weight [kg]	37.5
Construction type	Free standing model
Input connection	Fixed connection
Number of output connections fixed connection	1

ETIM - Technical features

USB interface	Yes
Suitable for network-management	Yes
USV- technology	Online
Overall efficiency [%]	91.5
Potential free switch contact	No
Auto shut down function	Yes

Logistics

GTIN/EAN	8027122573054
----------	---------------

Customs number	8504409590
Weight of the packing unit	37.5
Length of the packing unit	0.37
Width of the packing unit	0.19
Depth of the packing unit	0.32
Technical Characteristics	
Depth	370
Height	320
In/out	1/1
Output voltage	230
Rated frequency	50/50
Width	190
Sn	6
Pn	4.8
Conf	C1
Input voltage	230
Rate (min)	6
Rate (max)	6
Configuration	UPS Single Unit(s) with Bypass