



## Circuit breaker, PowerPacT J, 225A, 3 pole, 600VAC, 18kA, I-Line, thermal magnetic, 80%, ABC

JGA36225

Product availability: Stock - Normally stocked in distribution facility

Price\*: 3,968.00 USD

## Main

Range	PowerPact
product name	PowerPact J
Product or Component Type	Circuit breaker
Device Application	Distribution

## Complementary

Complementary		
Line Rated Current	225 A	
Number of Poles	3P	
Control Type	Toggle	
Breaking capacity code	G	
Breaking capacity	65 kA 240 V AC 50/60 Hz UL 489	
	35 kA 480 V AC 50/60 Hz UL 489	
	18 kA 600 V AC 50/60 Hz UL 489	
	20 kA 250 V DC UL 489	
	20 kA 500 V DC UL 489	
[Ue] rated operational voltage	600 V AC 50/60 Hz IEC 60947-3	
Network Frequency	50/60 Hz	
[Ics] rated service breaking	65 kA 220/240 V AC 50/60 Hz IEC 60947-2	
capacity	35 kA 380/440/415 V AC 50/60 Hz IEC 60947-2	
	18 kA 500/525 V AC 50/60 Hz IEC 60947-2	
	20 kA 250 V DC IEC 60947-2	
	20 kA 500 V DC IEC 60947-2	
[Uimp] rated impulse withstand voltage	8 kV IEC 60947-2	
Trip unit technology	Thermal-magnetic	
Magnetic tripping current	2250 A	
Magnetic hold current	1125 A	
Continuous current rating	80 %	
[Ui] rated insulation voltage	750 V IEC 60947-2	
Protection Type	Overload protection	
	Short-circuit protection	
Suitability for isolation	Yes IEC 60947-2	
Utilisation category	Category A	
AWG gauge	AWG 3/0350 kcmil aluminium/copper terminals	
Local signalling	Switched off (OFF) 1 trip indicator green)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Mounting mode	I-Line bracket)	
Mounting Support	Bracket	
Electrical connection	I-Line connection, line Lugs, load	
Terminal identifier	AL250JD	
Long time pick-up adjustment range	0.251 x ln	
Mounting Height	4.5 in (114.3 mm)	
Tightening torque	221.3 lbf.in (25 N.m) 0.10.3 in² (95185 mm²) (AWG 3/0350 kcmil)	
Number of slots	2 auxiliary switch OF plug-in) 1 alarm switch SD plug-in) 1 overcurrent trip switch SDE plug-in) 1 voltage release MN or MX plug-in)	
Power wire stripping length	1.0 in (25 mm)	
Height	7.5 in (191 mm)	
Width	4.09 in (104 mm)	
Depth	3.4 in (86 mm)	
Net Weight	5.3 lb(US) (2.4 kg)	
Phase connection	ABC	
Communication interface	Modbus Ethernet	
Circuit breaker application	HACR rated	

## **Environment**

Quality labels	CE
Standards	UL CSA NEMA NOM-003-SCFI-2000 IEC 60947-2
Product certifications	UL CSA NOM
IP degree of protection	Front cover IP40
Pollution degree	3 IEC 60947-1
Ambient air temperature for operation	-13158 °F (-2570 °C)
Ambient Air Temperature for Storage	-58185 °F (-5085 °C)
Operating altitude	< 6561.68 ft (2000 m) without derating 5000 m with derating

# Ordering and shipping details

Category	US10DE201117
Discount Schedule	0DE2
GTIN	785901795841
Returnability	Yes
Country of origin	MX

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.91 in (15.0 cm)
Package 1 Width	8.39 in (21.3 cm)
Package 1 Length	14.88 in (37.8 cm)
Package 1 Weight	6.66 lb(US) (3.02 kg)

## **Contractual warranty**

Warranty 18 months

# **Environmental Data**

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	1104
Environmental Disclosure	Product Environmental Profile

## **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

# **Use Again**

# Circularity Profile Removable battery No Take-back No

## **Technical Illustration**

## **Dimensions**

