Specifications

#### SQUARE D



# Circuit breaker, PowerPacT J, 150A, 3 pole, 600VAC, 25kA, lugs, thermal magnetic, 80%

JJL36150

Product availability: Stock - Normally stocked in distribution facility

## Price\*: 5,432.00 USD

## Main

Range	PowerPact
product name	PowerPact J
Product or Component Type	Circuit breaker
Device Application	Distribution

## Complementary

Complementary		
Line Rated Current	150 A	
Number of Poles	ЗР	
Control Type	Toggle	
Breaking capacity code	J	
Breaking capacity	100 kA 240 V AC 50/60 Hz UL 489 65 kA 480 V AC 50/60 Hz UL 489 25 kA 600 V AC 50/60 Hz UL 489 20 kA 250 V DC UL 489	
[Ue] rated operational voltage	600 V AC 50/60 Hz IEC 60947-3	
Network Frequency	50/60 Hz	
[Ics] rated service breaking capacity	65 kA 220/240 V AC 50/60 Hz IEC 60947-2 35 kA 380/440/415 V AC 50/60 Hz IEC 60947-2 18 kA 500/525 V AC 50/60 Hz IEC 60947-2 20 kA 250 V DC IEC 60947-2 20 kA 500 V DC IEC 60947-2	
[Uimp] rated impulse withstand voltage	8 kV IEC 60947-2	
Trip unit technology	Thermal-magnetic	
Magnetic tripping current	1750 A	
Magnetic hold current	750 A	
Continuous current rating	80 %	
[Ui] rated insulation voltage	750 V IEC 60947-2	
Protection Type	Overload protection Short-circuit protection	
Suitability for isolation	Yes IEC 60947-2	
Utilisation category	Category A	
AWG gauge	AWG 4AWG 4/0 aluminium/copper terminal	
Local signalling	Switched off (OFF) 1 trip indicator green)	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Unit mount lug)	
Lug	
Lugs, line Lugs, load	
AL175JD	
0.251 x ln	
4.5 in (114.3 mm)	
221.3 lbf.in (25 N.m) 0.040.1 in <sup>2</sup> (2595 mm <sup>2</sup> ) (AWG 4AWG 4/0)	
2 auxiliary switch OF plug-in) 1 alarm switch SD plug-in) 1 overcurrent trip switch SDE plug-in) 1 voltage release MN or MX plug-in)	
1.0 in (25 mm)	
7.5 in (191 mm)	
4.09 in (104 mm)	
3.4 in (86 mm)	
5.3 lb(US) (2.4 kg)	
BA	
Modbus Ethernet	
HACR rated	

## Environment

Quality labels	CE	
Standards	UL CSA NEMA NOM-003-SCFI-2000 IEC 60947-2	
Product certifications	UL CSA NOM	
IP degree of protection	Front cover IP40	
Pollution degree	3 IEC 60947-1	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Ambient Air Temperature for Storage	-58185 °F (-5085 °C)	
Operating altitude	< 6561.68 ft (2000 m) without derating 5000 m with derating	

# Ordering and shipping details

Category	US10DE201115	
Discount Schedule	0DE2	
GTIN	785901955931	
Returnability	Yes	
Country of origin	MX	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.71 in (14.5 cm)
Package 1 Width	7.28 in (18.5 cm)
Package 1 Length	8.90 in (22.6 cm)
Package 1 Weight	4.81 lb(US) (2.18 kg)

## **Contractual warranty**

Warranty

18 months

# Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability  $\geq$ 

${\mathcal Q}$ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	832
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

$^{\circlearrowright}$ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No

## Product data sheet

## **Dimensions Drawings**

### Approximate Dimensions

