

Product data sheet

Specifications



Electronic time delay auxiliary contact block, TeSys K, 1C/O, on delay 1-30s, front, control 24...48V AC/DC

LA2KT2E

Product availability : Stock - Normally stocked in distribution facility

Price* : 78.72 USD

Main

| | |
|---|--|
| Range | TeSys |
| Product name | TeSys K |
| Product or Component Type | Time delay auxiliary contact block |
| Device short name | LA1 |
| Range compatibility | TeSys K LC1K TeSys K CA2K TeSys K CA3K TeSys K CA4K |
| Mounting Location | Front |
| Pole contact composition | 1 C/O |
| Contacts operation | Time delay |
| Timer type | On delay |
| Time delay range | 1...30 s |
| [Ue] rated operational voltage | 24...48 V AC/DC control circuit 240 V AC signalling circuit |
| Rated operational voltage limits | 0.85...1.1 Uc |
| [Ith] conventional free air thermal current | 2 A signalling circuit |
| Standards | EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 |
| Product Certifications | UL CSA CE UKCA |

Complementary

| | |
|-------------------------|---|
| Insulation resistance | > 10 MOhm |
| Connections - terminals | slip-on terminals |
| Reset time | 1.5 s during time delay 0.5 s after time delay |
| Height | 1.06 in (27 mm) |
| Width | 1.50 in (38 mm) |

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|------------|-----------------------|
| Depth | 1.50 in (38 mm) |
| Net Weight | 0.09 lb(US) (0.04 kg) |

Environment

| | |
|---------------------------------------|------------------------------|
| Environmental characteristic | Normal environment |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Protective treatment | TC IEC 60068 |
| Ambient air temperature for operation | 14...140 °F (-10...60 °C) |

Ordering and shipping details

| | |
|-------------------|-------------------------------|
| Category | 22341-CONTACTOR,D,K,&F ACCESS |
| Discount Schedule | I12 |
| GTIN | 3389110230048 |
| Returnability | No |
| Country of origin | TN |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.97 in (5.000 cm) |
| Package 1 Width | 1.89 in (4.800 cm) |
| Package 1 Length | 1.89 in (4.800 cm) |
| Package 1 Weight | 1.41 oz (40.000 g) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 70 |
| Package 2 Height | 5.91 in (15.000 cm) |
| Package 2 Width | 11.81 in (30.000 cm) |
| Package 2 Length | 15.75 in (40.000 cm) |
| Package 2 Weight | 6.86 lb(US) (3.110 kg) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

Warranty18 months

Recommended replacement(s)