



Terminal shroud, TeSys Giga contactor, for LC1G630-800, 3 Pole, IP20

LA9G3703

Main

Product or component type	Terminal shroud
Accessory / separate part type	Installation accessories
poles description	3P
Quantity per set	Set of 1

Complementary

Height	164 mm	
Width	211 mm	
Depth	115 mm	
Net weight	0.165 kg	
IP degree of protection	IP20 conforming to IEC 60529	
Product compatibility	LC1G630800	

Environment

Pollution degree	3 conforming to IEC 60947-1
Standards	EN/IEC 60947-1 UL 60947-1 CSA C22.2 No 60947-1 GB/T 14048
Operating altitude	3000 m without derating 5000 m with derating factor
Ambient air temperature for storage	-4060 °C
Ambient air temperature for operation	-6080 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15 cm
Package 1 Width	30 cm
Package 1 Length	40 cm
Package 1 Weight	966 g



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Mercury Free	
Ø	Rohs Exemption Information	Yes
②	Pvc Free	
⊘	Halogen Free Plastic Parts Product	

Certifications & Standards

Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information