

Product data sheet

Specifications



Circuit breaker, LA, 150A, 3 pole,
600VAC, 22kA, 250VDC, 10kA,
lugs, thermal magnetic

LAL36150

Product availability: Non-Stock - Not normally stocked in
distribution facility

Price*: 4,619.00 USD

Main

| | |
|---------------------------|------------------|
| Product or Component Type | Circuit breaker |
| Trip Unit Technology | Thermal-magnetic |

Complementary

| | |
|-----------------------------|--|
| Line Rated Current | 150 A |
| Number of Poles | 3P |
| Mounting Mode | Unit mount |
| Magnetic Hold Current | 750 A |
| Magnetic Tripping Current | 1500 A |
| Electrical connection | Lugs, load Lugs, line |
| Terminal identifier | AL400LA |
| Tightening torque | 115.06 lbf.in (13 N.m) 0.07...0.5 in² (42...304 mm²) (AWG 1...600 kcmil) 115.06 lbf.in (13 N.m) 0.07...0.2 in² (42...127 mm²) (AWG 1...250 kcmil) |
| Height | 11 in (279.4 mm) |
| Width | 6 in (152.4 mm) |
| Depth | 5.84 in (148.34 mm) |
| Circuit breaker application | HACR rated |

Environment

| | |
|----------------|-------------------------|
| Certifications | IEC CSA UL Listed |
|----------------|-------------------------|

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US10DE200935 |
| Discount Schedule | 0DE2 |
| GTIN | 785901563228 |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|------------------------------|--------------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.44 in (21.433 cm) |
| Package 1 Width | 11.13 in (28.258 cm) |
| Package 1 Length | 17.13 in (43.498 cm) |
| Package 1 Weight | 15.906 lb(US) (7.215 kg) |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

| Environmental footprint | |
|--------------------------|---|
| Environmental Disclosure | Product Environmental Profile |

Use Better

| Materials and Substances | |
|--|--|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Compliant with Exemptions |
| SCIP Number | 45160aaa-1457-439f-bca7-7bd5246ac23e |
| REACH Regulation | REACH Declaration |
| China RoHS Regulation | China RoHS declaration |
| California proposition 65 | WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| PVC free | Yes |

Use Again

| Repack and remanufacture | |
|-----------------------------|--|
| Circularity Profile | No need of specific recycling operations |
| Halogen content performance | Halogen free plastic parts product |
| Take-back | No |