Product datasheet

Specification





TeSys D contactor - 3P(3 NO) - AC-3 - <= 440 V 38 A - 120 V AC 50/60 Hz coil

LC1D38G7

Main

| Range | TeSys TeSys Deca | |
|--------------------------------|---|--|
| Range of product | TeSys Deca | |
| Product or component type | Contactor | |
| Device short name | LC1D | |
| contactor application | Resistive load Motor control | |
| Utilisation category | AC-4 AC-1 AC-3 AC-3e | |
| poles description | 3P | |
| [Ue] rated operational voltage | Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC | |
| [le] rated operational current | 50 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 38 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 38 A (at <60 °C) at <= 440 V AC AC-3e for power circuit | |
| [Uc] control circuit voltage | 120 V AC 50/60 Hz | |

Complementary

| Motor power kW | 18.5 kW at 500 V AC 50/60 Hz (AC-3) | |
|-------------------------------------|---|--|
| | 18.5 kW at 660690 V AC 50/60 Hz (AC-3) | |
| | 7.5 kW at 400 V AC 50/60 Hz (AC-4) | |
| | 18.5 kW at 380400 V AC 50/60 Hz (AC-3) | |
| | 9 kW at 220230 V AC 50/60 Hz (AC-3) | |
| | 18.5 kW at 415440 V AC 50/60 Hz (AC-3) | |
| | 18.5 kW at 500 V AC 50/60 Hz (AC-3e) | |
| | 18.5 kW at 660690 V AC 50/60 Hz (AC-3e) | |
| | 18.5 kW at 380400 V AC 50/60 Hz (AC-3e) | |
| | 9 kW at 220230 V AC 50/60 Hz (AC-3e) | |
| | 18.5 kW at 415440 V AC 50/60 Hz (AC-3e) | |
| Motor power hp | 10 hp at 230/240 V AC 50/60 Hz for 3 phases motors | |
| | 10 hp at 200/208 V AC 50/60 Hz for 3 phases motors | |
| | 5 hp at 240 V AC 50/60 Hz for 1 phase motors | |
| | 20 hp at 480 V AC 50/60 Hz for 3 phases motors | |
| | 25 hp at 600 V AC 50/60 Hz for 3 phases motors | |
| Compatibility code | LC1D | |
| Pole contact composition | 3 NO | |
| Protective cover | With | |
| [Ith] conventional free air thermal | 10 A (at 60 °C) for signalling circuit | |
| current | 50 A (at 60 °C) for power circuit | |
| Irms rated making capacity | 140 A AC for signalling circuit conforming to IEC 60947-5-1 | |
| | 250 A DC for signalling circuit conforming to IEC 60947-5-1 | |
| | 550 A at 440 V for power circuit conforming to IEC 60947 | |
| | • | |

| Rated breaking capacity | 550 A at 440 V for power circuit conforming to IEC 60947 |
|--|--|
| [lcw] rated short-time withstand | 60 A 40 °C - 10 min for power circuit |
| current | 430 A 40 °C - 1 s for power circuit |
| | 150 A 40 °C - 1 min for power circuit |
| | 310 A 40 °C - 10 s for power circuit |
| | 100 A - 1 s for signalling circuit |
| | 120 A - 500 ms for signalling circuit |
| | 140 A - 100 ms for signalling circuit |
| Associated fuse rating | 10 A gG for signalling circuit conforming to IEC 60947-5-1 |
| | 63 A gG at <= 690 V coordination type 1 for power circuit |
| | 63 A gG at <= 690 V coordination type 2 for power circuit |
| Average impedance | 2 mOhm - Ith 50 A 50 Hz for power circuit |
| Power dissipation per pole | 5 W AC-1 |
| | 3 W AC-3 |
| | 3 W AC-3e |
| [Ui] rated insulation voltage | Power circuit: 600 V CSA certified |
| | Power circuit: 600 V UL certified |
| | Signalling circuit: 690 V conforming to IEC 60947-1 |
| | Signalling circuit: 600 V CSA certified |
| | Signalling circuit: 600 V UL certified |
| | Power circuit: 690 V conforming to IEC 60947-4-1 |
| Overvoltage category | III |
| Pollution degree | 3 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947 |
| Safety reliability level | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 |
| | B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO |
| | 13849-1 |
| Mechanical durability | 15 Mcycles |
| Electrical durability | 1.4 Mcycles 50 A AC-1 at Ue <= 440 V |
| | 1.4 Mcycles 38 A AC-3 at Ue <= 440 V |
| | 1.4 Mcycles 38 A AC-3e at Ue <= 440 V |
| Control circuit type | AC at 50/60 Hz |
| Coil technology | Without built-in suppressor module |
| Control circuit voltage limits | 0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz |
| - | 0.81.1 Uc (-4060 °C):operational AC 50 Hz |
| | 0.851.1 Uc (-4060 °C):operational AC 60 Hz |
| | 11.1 Uc (6070 °C):operational AC 50/60 Hz |
| Inrush power in VA | 70 VA 60 Hz cos phi 0.75 (at 20 °C) |
| | 70 VA 50 Hz cos phi 0.75 (at 20 °C) |
| Hold-in power consumption in VA | 7.5 VA 60 Hz cos phi 0.3 (at 20 °C) |
| , | 7 VA 50 Hz cos phi 0.3 (at 20 °C) |
| Heat dissipation | 23 W at 50/60 Hz |
| Operating time | 419 ms opening |
| - | 1222 ms closing |
| Maximum operating rate | 3600 cyc/h 60 °C |
| | 5555 575 50 |

| Connections - terminals | Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with cable end |
|-------------------------------|---|
| | Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without |
| | cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without |
| | cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable |
| | end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without |
| | cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid without |
| | cable end Power circuit: screw clamp terminals 1 2.510 mm² - cable stiffness: flexible without |
| | cable end |
| | Power circuit: screw clamp terminals 2 2.510 mm² - cable stiffness: flexible without cable end |
| | Power circuit: screw clamp terminals 1 110 mm ² - cable stiffness: flexible with cable end |
| | Power circuit: screw clamp terminals 2 1.56 mm ² - cable stiffness: flexible with cable end |
| | Power circuit: screw clamp terminals 1 1.510 mm² - cable stiffness: solid without cable end |
| | Power circuit: screw clamp terminals 2 2.510 mm ² - cable stiffness: solid without cable end |
| Timbéonia a écuario | |
| Tightening torque | Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 |
| Auxiliary contact composition | 1 NO + 1 NC |
| Auxiliary contacts type | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1 |
| Signalling circuit frequency | 25400 Hz |
| Minimum switching voltage | 17 V for signalling circuit |
| Minimum switching current | 5 mA for signalling circuit |
| Insulation resistance | > 10 MOhm for signalling circuit |
| Non-overlap time | 1.5 ms on de-energisation between NC and NO contact1.5 ms on energisation between NC and NO contact |
| Mounting support | Rail Plate |
| Environment | |
| Standards | 00A 000 0 N: 44 |
| Standards | CSA C22.2 No 14 EN 60947-4-1 |
| | EN 60947-5-1 IEC 60947-4-1 |
| | IEC 60947-5-1 |
| | UL 508 IEC 60335-1 |
| Product certifications | DNV |
| | GL CCC |
| | LROS (Lloyds register of shipping) |
| | RINA |
| | BV GOST |
| | UL |
| | CSA CB |
| IP degree of protection | IP20 front face conforming to IEC 60529 |
| Protective treatment | TH conforming to IEC 60068-2-30 |
| Climatic withstand | conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat |
| | |

| Permissible ambient air temperature around the device | -4060 °C 6070 °C with derating | |
|---|--|--|
| Operating altitude | 03000 m | |
| Fire resistance | 850 °C conforming to IEC 60695-2-1 | |
| Flame retardance | V1 conforming to UL 94 | |
| Mechanical robustness | Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms) Shocks contactor open (8 Gn for 11 ms) | |
| Height | 85 mm | |
| Width | 45 mm | |
| Depth | 92 mm | |
| Net weight | 0.38 kg | |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|----------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 11.1 cm |
| Package 1 Width | 9.1 cm |
| Package 1 Length | 4.9 cm |
| Package 1 Weight | 412.0 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 20 |
| Package 2 Height | 15.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 8.695 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Rohs Exemption Information

Yes



Pvc Free

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |