

Product data sheet

Specifications



contactor, TeSys F, 4P(4NO), AC-1,
<=440V 1600A with coil LX1/LX9
110...500V AC 40/400Hz, LX4
110...440V DC

LC1F7804

Main

Range	TeSys
Product name	TeSys F
Product or component type	Contactor
Device short name	LC1F
Contactor application	Resistive load
Utilisation category	AC-1
Poles description	4P
Power pole contact composition	4 NO
[Ue] rated operational voltage	<= 1000 V AC 50/60 Hz <= 460 V DC
[Ie] rated operational current	1600 A (at <40 °C) at <= 440 V AC AC-1

Complementary

[Uc] control circuit voltage	110...500 V AC 40...400 Hz with LX1/LX9 coil 48...440 V DC with LX4 coil
[Uimp] rated impulse withstand voltage	8 kV
Overvoltage category	III
[Ith] conventional free air thermal current	1600 A (at 40 °C)
Irms rated making capacity	7800 A AC conforming to IEC 60947-4-1
Rated breaking capacity	6240 A conforming to IEC 60947-4-1
[Icw] rated short-time withstand current	3000 A 40 °C - 3 min 6250 A 40 °C - 10 s 5600 A 40 °C - 30 s 4600 A 40 °C - 1 min 2200 A 40 °C - 10 min
Associated fuse rating	800 A aM at <= 440 V 1600 A gG at <= 440 V
Average impedance	0.1 mOhm - Ith 1600 A 50 Hz
[Ui] rated insulation voltage	1000 V conforming to IEC 60947-4-1 1500 V conforming to VDE 0110 group C
Power dissipation per pole	250 W AC-1
Control circuit voltage limits	Operational: 0.85...1.1 Uc AC 40...400 Hz with LX1/LX9 coil Drop-out: 0.2...0.4 Uc AC 40...400 Hz with LX1/LX9 coil Operational: 0.85...1.1 Uc DC with LX4 coil

	Drop-out: 0.2...0.4 Uc DC with LX4 coil
Heat dissipation	22 W
Operating time	40...80 ms closing for with LX1/LX9 coil 130...230 ms opening for with LX1/LX9 coil 70...80 ms closing for with LX4 coil 100...130 ms opening for with LX4 coil
Mounting support	Plate
Standards	IEC 60947-1 IEC 60947-4-1 EN 60947-1 JIS C8201-4-1 EN 60947-4-1
Product certifications	UL LROS (Lloyds register of shipping) RINA DNV CCC BV CB ABS UKCA
Connections - terminals	Power circuit: bar 2 cable(s) - busbar cross section: 100 x 5 mm Power circuit: bolted connection Control circuit: screw clamp terminals 1 cable(s) 1...4 mm²flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...4 mm²flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm²flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm²solid without cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm² Control circuit: screw clamp terminals 2 cable(s) 1...4 mm²
Tightening torque	Power circuit: 58 N.m Control circuit: 1.2 N.m
Mechanical durability	5 Mcycles
Inrush power in VA	1900...2300 VA, 40...400 Hz cos phi 0.9 (at 20 °C)with LX1/LX9 coil 1960...2420 VA (at 20 °C)with LX4 coil
Hold-in power consumption in VA	44...55 VA, 40...400 Hz cos phi 0.9 (at 20 °C)with LX1/LX9 coil 42...52 VA (at 20 °C)with LX4 coil
Maximum operating rate	600 cyc/h 55 °C
Compatibility code	LC1F

Environment

IP degree of protection	IP20 front face with shrouds conforming to IEC 60529 IP20 front face with shrouds conforming to VDE 0106
Protective treatment	TH
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C
Permissible ambient air temperature around the device	-40...70 °C
Operating altitude	3000 m without derating
Mechanical robustness	Vibrations contactor open: 2.5 Gn, 5...300 Hz Vibrations contactor closed: 5.5 Gn, 5...300 Hz Shocks contactor open: 5 Gn for 1/2 sine wave (11 ms) Shocks contactor closed: 15 Gn for 1/2 sine wave (11 ms)
Height	434 mm
Width	862 mm
Depth	255 mm
Net weight	48 kg

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Height	41.0 cm
Package 1 Width	115.0 cm
Package 1 Length	44.0 cm
Package 1 Weight	47.5 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	2
Package 2 Height	85.0 cm
Package 2 Width	120.0 cm
Package 2 Length	80.0 cm
Package 2 Weight	142.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)