# **Product datasheet**

Specification





Contactor, TeSys K, 3P, AC-3/AC-3e,<=440V 9A, aux. 1NO, 230...240V AC coil

LC1K0910U7

### Main

Range	TeSys	
Product Or Component Type	Contactor	
Device Application	Control	
Contactor Application	Resistive load Motor control	

Utilisation Category	AC-3	
Othisation Category	AC-3 AC-3e	
	AC-3e AC-1	
	AC-1 AC-4	
	AC-4	
Poles Description	3P	
Power Pole Contact Composition	3 NO	
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC <= 400 Hz	
	Signalling circuit: <= 690 V AC <= 400 Hz	
[le] Rated Operational Current	9 A (at <60 °C) at <= 440 V AC AC-3 for power circuit	
	9 A (at <60 °C) at <= 440 V AC AC-3e for power circuit	
	20 A (at <60 °C) at <= 690 V AC AC-1 for power circuit	
Control Circuit Type	AC at 50/60 Hz	
[Uc] Control Circuit Voltage	230240 V AC 50/60 Hz	
Motor Power Kw	2.2 kW at 220230 V AC 50/60 Hz AC-3	
	4 kW at 380415 V AC 50/60 Hz AC-3	
	4 kW at 440/690 V AC 50/60 Hz AC-3	
	2.2 kW at 220230 V AC 50/60 Hz AC-3e	
	4 kW at 380415 V AC 50/60 Hz AC-3e	
	4 kW at 440/690 V AC 50/60 Hz AC-3e	
	2.2 kW at 220230 V AC 50/60 Hz AC-4	
	4 kW at 380415 V AC 50/60 Hz AC-4	
	4 kW at 440/690 V AC 50/60 Hz AC-4	
Auxiliary Contact Composition	1 NO	
[Uimp] Rated Impulse Withstand Voltage	8 kV	
Overvoltage Category	III	
[Ith] Conventional Free Air	20 A (at 60 °C) for power circuit	
Thermal Current	10 A (at 50 °C) for signalling circuit	
Irms Rated Making Capacity	110 A AC for power circuit conforming to IEC 60947	
	110 A AC for signalling circuit conforming to IEC 60947	
Rated Breaking Capacity	110 A at 220230 V conforming to IEC 60947	
<u> </u>	110 A at 380400 V conforming to IEC 60947	
	110 A at 415 V conforming to IEC 60947	
	110 A at 440 V conforming to IEC 60947	
	80 A at 500 V conforming to IEC 60947	

[Icw] Rated Short-Time Withstand	90 A 50 °C - 1 s for power circuit
Current	85 A 50 °C - 5 s for power circuit
	80 A 50 °C - 10 s for power circuit
	60 A 50 °C - 30 s for power circuit 45 A 50 °C - 1 min for power circuit
	40 A 50 °C - 3 min for power circuit
	20 A 50 °C - >= 15 min for power circuit
	80 A - 1 s for signalling circuit
	90 A - 500 ms for signalling circuit
	110 A - 100 ms for signalling circuit
Associated Fuse Rating	25 A gG at <= 440 V for power circuit
-	25 A aM for power circuit
	10 A gG for signalling circuit conforming to IEC 60947
	10 A gG for signalling circuit conforming to VDE 0660
Average Impedance	3 mOhm - Ith 20 A 50 Hz for power circuit
Insulation Resistance	> 10 MOhm for signalling circuit
Inrush Power In Va	30 VA (at 20 °C)
Hold-In Power Consumption In Va	4.5 VA (at 20 °C)
Heat Dissipation	1.3 W
Control Circuit Voltage Limits	Operational: 0.81.15 Uc (at <50 °C)
	Drop-out: >= 0.20 Uc (at <50 °C)
Connections - Terminals	Screw clamp terminals 1 cable(s) 1.54 mm²solid
Commodation Terminals	Screw clamp terminals 1 cable(s) 1.54 mm²flexible without cable end
	Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end
	Screw clamp terminals 2 cable(s) 1.54 mm²solid
	Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end
	Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end
Maximum Operating Rate	3600 cyc/h
Auxiliary Contacts Type	type instantaneous 1 NO
Signalling Circuit Frequency	<= 400 Hz
Minimum Switching Current	5 mA for signalling circuit
Minimum Switching Voltage	17 V for signalling circuit
Operating Time	1020 ms coil de-energisation and NO opening
	1020 ms coil energisation and NO closing
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1
	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO
	13849-1
Non Overlap Distance	0.5 mm
Mechanical Durability	10 Mcycles
Electrical Durability	1.3 Mcycles 9 A AC-3 at Ue <= 440 V
•	1.3 Mcycles 9 A AC-3e at Ue <= 440 V
	0.16 Mcycles 20 A AC-1 at Ue <= 690 V
	0.02 Mcycles 54 A AC-4 at Ue <= 440 V
Mechanical Robustness	Shocks contactor closed, on X axis: 10 Gn for 11 ms conforming to IEC 60068-2-27
	Shocks contactor closed, on Y axis: 15 Gn for 11 ms conforming to IEC 60068-2-27
	Shocks contactor closed, on Z axis: 15 Gn for 11 ms conforming to IEC 60068-2-27
	Shocks contactor opened, on X axis: 6 Gn for 11 ms conforming to IEC 60068-2-27
	Shocks contactor opened, on Y axis: 10 Gn for 11 ms conforming to IEC 60068-2-27
	Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2-27  Vibrations contactor closed: 4 Gn. 5, 300 Hz conforming to IEC 60068-2-6
	Vibrations contactor closed: 4 Gn, 5300 Hz conforming to IEC 60068-2-6 Vibrations contactor opened: 2 Gn, 5300 Hz conforming to IEC 60068-2-6
Height	58 mm
Width	45 mm
Depth	57 mm

### **Environment**

Standards	EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1
Product Certifications	CB Scheme CCC UL CSA EAC CE
Protective Treatment	TC conforming to IEC 60068 TC conforming to DIN 50016
Operating Altitude	2000 m without derating
Flame Retardance	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.500 cm
Package 1 Width	6.200 cm
Package 1 Length	4.800 cm
Package 1 Weight	177.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	50
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	9.368 kg

## **Contractual warranty**

Warranty 18 months

### Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>⊘</b>	Reach Free Of Svhc	
<b>9</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information