SQUARE D



Circuit breaker, PowerPacT L, 600A, 3 pole, 600VAC, 25kA, I-Line, MicroLogic 6.3A, 80%, ABC

LJA36600U44X

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 14,332.00 USD

Main

Range	PowerPact
product name	PowerPact L
Device short name	L-Frame
Product or Component Type	Circuit breaker
Device Application	Distribution

Complementary

Line Rated Current	600 A	
Number of Poles	3P	
Control Type	Toggle	
Breaking capacity code	J	
Breaking capacity	100 kA 240 V AC 50/60 Hz UL 489 65 kA 480 V AC 50/60 Hz UL 489 25 kA 600 V AC 50/60 Hz UL 489 20 kA 250 V DC UL 489	
[Ue] rated operational voltage	600 V AC 50/60 Hz IEC 60947-3	
Network Frequency	50/60 Hz	
[Ics] rated service breaking capacity	65 kA 220/240 V AC 50/60 Hz IEC 60947-2 35 kA 380/440/415 V AC 50/60 Hz IEC 60947-2 18 kA 500/525 V AC 50/60 Hz IEC 60947-2 20 kA 250 V DC IEC 60947-2 20 kA 500 V DC IEC 60947-2	
[Uimp] rated impulse withstand voltage	8 kV IEC 60947-2	
Trip unit technology	Electronic, ammeter, MicroLogic 6.3 A, LSIG	
Continuous current rating	80 %	
[Ui] rated insulation voltage	750 V IEC 60947-2	
Trip unit name	MicroLogic 6.3 A	
Protection technology	Current limiter	
Suitability for isolation	Yes IEC 60947-2	
Utilisation category	Category A	
AWG gauge	2 x AWG 2/0500 kcmil aluminium/copper	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Local signalling	Ready 1 LED green) Alarm 1 LED 90 % Ir orange) Alarm LED 105 % Ir red)	
	Switched off (OFF) 1 trip indicator green)	
Mounting mode	I-Line bracket)	
Mounting Support	Bracket	
Electrical connection	I-Line connection, line Lugs, load	
Terminal identifier	AL600LF52K3	
Long time pick-up adjustment range	0.251 x ln	
Mounting Height	6 in (152.4 mm)	
Tightening torque	442.5 lbf.in (50 N.m) 0.10.4 in² (70240 mm²) (2 x AWG 2/0500 kcmil) 442.5 lbf.in (50 N.m) 0.050.5 in² (35300 mm²) (AWG 2600 kcmil)	
Number of slots	2 auxiliary switch OF plug-in) 1 alarm switch SD plug-in) 1 overcurrent trip switch SDE plug-in) 1 voltage release MN or MX plug-in)	
Power wire stripping length	1.2 in (31 mm)	
Color	Black	
Height	13.4 in (340 mm)	
Width	5.5 in (140 mm)	
Depth	4.3 in (110 mm)	
Product Weight	13.7 lb(US) (6.2 kg)	
Phase connection	ABC	
Communication interface	Modbus Ethernet	
Circuit breaker application	HACR rated	

Environment

Standards	UL CSA NEMA NOM-003-SCFI-2000 IEC 60947-2	
Product certifications	UL CSA NOM	
IP degree of protection	Front cover IP40	
Pollution degree	3 IEC 60947-1	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Ambient Air Temperature for Storage	-58185 °F (-5085 °C)	
Operating altitude	< 6561.68 ft (2000 m) without derating 5000 m with derating	

Ordering and shipping details

Category	US10DE201118
Discount Schedule	0DE2
GTIN	785901486985
Returnability	Yes

Country of origin US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.75 in (22.225 cm)
Package 1 Width	10.75 in (27.305 cm)
Package 1 Length	19.50 in (49.53 cm)
Package 1 Weight	17.000 lb(US) (7.711 kg)

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	1672
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	No
Take-back	No